

# **S32 DESIGN STUDIO IDE (S32DS)**



The complimentary S32 Design Studio IDE (S32DS) is a comprehensive enablement environment for automotive and industrial applications with no code-size limitations.

# **OVERVIEW**

The S32DS enables editing, compiling, debugging and tracing of user's applications. Based on open-source software, including Eclipse IDE, GNU Compiler Collection (GCC) and GNU Debugger (GDB), the S32 Design Studio IDE offers software developers a straightforward development tool.

NXP software included along with the S32 Design Studio IDE completes the comprehensive enablement environment and reduces development time.

#### **S32DS FEATURES**

- S32 Configuration Tools for pin functions, clocks, peripheral drivers and FreeRTOS
- Boot Tools: DCD Tool, IVT Tool, QuadSPI Tool
- DDR tools
- S32 Debugger for S32 Platform and S32 Debug Probe support
- New project wizard to create bare metal or software development kit (SDK) projects
- Integrated runtime software: Real-Time Drivers, S32 SDK, Vision SDK, and Radar SDK
- Advanced FreeRTOS kernel-aware debug support
- Peripherals register view
- Assembly language supported, together with C and C++
- Supports Eclipse plug-ins from the Eclipse ecosystem or from partners
- Supported host operating systems\*:
  - Microsoft<sup>®</sup> Windows<sup>®</sup> 10 with 32&64-bit binaries running on 64-bit OS
  - Ubuntu 20.04 (64 bit)
    - \*Versions prior to S32DS 3.5 supports OS (Windows 7/8, Ubuntu 16.04 (64-bit), 18.04 (64-bit), Debian 8 (64-bit), CentOS 7 (64-bit))

# FACT SHEET S32DS

# **S32DS SUPPORTED DEVICES**

	\$32D\$	S32DS	S32DS
	for S32 Platform	for Arm®	for Power Architecture®
SUPPORTED PRODUCTS	\$326 \$32K3 \$32K1 \$32S24 \$32Z2/E2 \$32V \$32R41 \$32R45	S32K1 KEA MAC57D54H	S32R294, S32R274, S32R264 MPC57xx MPC56xx
INTEGRATED NXP TOOLS	S32 Configuration Tool Pins Wizard Clocks configuration Peripheral/Drivers configuration DCD configuration IVT configuration QuadSPI configuration DDR configuration S32 Flash Tool FreeMASTER	Processor Expert Pins Wizard Peripheral/Driver configuration FreeMASTER	Processor Expert Fins Wizard Peripheral/Driver configuration FreeMASTER
INTEGRATED NXP SOFTWARE	S32 RTD S32 SDK FreeRTOS AMMCLib Vision SDK Linux® BSP	S32K1 SDK FreeRTOS AMMCLib for KEA and S32K KEA SDK MQX OS/MQX drivers for MAC57D54H	S32 SDK for MPC57xx and S32R FreeRTOS AMMCLib for MCP5xxx Radar SDK
COMPILERS	NXP GCC 10.2* NXP GCC 9.2* NXP GCC 6.3.1* Green Hills	NXP GCC 6.3.1* GCC 4.9* Green Hills IAR	NXP GCC 4.9* Green Hills Diab
DEBUGGERS	Built-in GDB interface: S32 Debugger/S32 Debug Probe P&E Multilink/Cyclone/ Open SDA Segger J-Link Lauterbach iSystem IAR	Built-in GDB interface:  - P&E /Multilink/Cyclone/ Open SDA  - Segger J-Link  • Lauterbach  • iSystem  • IAR	Built-in GDB interface:  - P&E Multilink/Cyclone/ Open SDA  • Lauterbach • iSystem, • PLS
DEDICATED TOOLS	Vision:  NXP APU Compiler  ISP Assembler  ISP and APEX graph tools  Radar:  SPT Visualization Tools (Timeline, Memory)  SPT assembler, explorer, graph tool		Radar:  • SPT assembler  • SPT explorer  • SPT graph tool


<sup>\*</sup>integrated

#### **GET STARTED WITH S32 DESIGN STUDIO IDE:**

Download it now: www.nxp.com/s32Ds

Join our S32DS online community:

https://community.nxp.com/t5/S32-Design-Studio/bd-p/s32ds



www.nxp.com

#### **DEBUGGER**

The S32 Debugger provides all the standard debugging features critical for testing and locating bugs in your application. It is dedicated to NXP microprocessors and accelerators and is available at the first customer silicon samples.

The S32 Debugger, as an essential part of the S32 Design Studio, is designed to work in conjunction with the S32 Debug Probe and NXP Automotive processors to accelerate all phases of project development.

## **S32 DEBUGGER FEATURES**

- Full integration within S32 Design Studio IDE using GDB interface in Eclipse supporting all standard debug features
- Support for all Arm cores and accelerator cores
- · Support for concurrent multicore debugging
- Integrated Flash programmer for Flash over JTAG
- Access to core and peripheral registers through IDE views
- Low level command line interface, GDB python scripting
- · Secured device debugging
- Trace Support on Arm Cores with Trace/Profiling Views
- OS aware debugging for FreeRTOS and AUTOSAR/OSEK OS
- · Supported host operating systems\*:
  - Microsoft<sup>®</sup> Windows<sup>®</sup> 10 with 32&64-bit binaries running on 64-bit OS
  - Ubuntu 20.04 (64 bit)
    - \*Versions prior to S32DS 3.5 supports OS (Windows 7/8, Ubuntu 16.04 (64-bit), 18.04 (64-bit), Debian 8 (64-bit), CentOS 7 (64-bit))

#### **S32 DEBUGGER SUPPORTED DEVICES**

SUPPORTED	CORES	FLASH	DEBUG HW
DEVICES	Arm/Accelerator /Trace	Type/ Part No.	
\$32G	Arm Cortex- A53 Arm Cortex-M7	QSPI Flash: MX25UW12A45G MX25UM51245G	S32 Debug Probe
	Accelerator: LLCE Trace:		
	Cortex-A53		
\$32V23X	Arm Cortex- A53 Arm Cortex-M4 Accelerator: APEX, ISP Trace: Cortex-A53	QSPI Flash: \$26KL512S	S32 Debug Probe
\$32\$247	Arm Cortex-R52	Embedded Flash: C55_AE QSPI Flash: MX25UW12A45G	S32 Debug Probe GreenBox II on-board CMSISDAP
\$32Z2/E2	Arm Cortex- R52, Cortex M33 Accelerator: CEVA, SPF2 Trace: Cortex-R52 Cortex-M33	QSPI Flash: \$26HS5I2 MT25QL256	S32 Debug Probe
S32R45	Arm Cortex-A53 Arm Cortex-M7 Accelerator: LAX, SPT, Tensilica BBE Trace: Cortex-A53	QSPI Flash: MX25UM51245G	S32 Debug Probe
\$32R41	Arm Cortex-A53 Arm Cortex-M7 Accelerator: SPT, Tensilica BBE	QSPI Flash: W25Q64J	S32 Debug Probe

## **S32 DEBUG PROBE**

S32 Debug Probe (S32DBGPROBE) enables NXP target system debugging via a standard debug port while connected to a developer's workstation via Ethernet or USB.

S32DBGPROBE may also be referred to by industry- standard terms such as a probe, JTAG probe, JTAG emulator or target probe.

S32 Debug Probe can be ordered at nxp.com or from an authorized NXP distributor.

Visit www.nxp.com/S32DebugProbe for more information



## QUALITY, STANDARD COMPLIANCE AND TESTING APPROACH

S32 Design Studio IDE is developed according to NXP Software Development Process that is compliant with IATF 16949 and ISO 9001.

# www.nxp.com/S32DS

NXP, the NXP logo and Processor Expert are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Microsoft and Windows are registered trademarks of the Microsoft Corporation. Arm is a trademark or registered trademark of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.

Document Number: \$32DSIDEPAFS REV 7