


TOL.GEN +/-0.1mm		STANDARD NFC 93-713	
Basic MATERIAL,BOARD Thickness:		FR4,16/10mm	
Basic Copper thickness:		17,5u	
MANUFACTURING Level <input type="text" value="5"/>			
SINGLE LAYER		<input type="checkbox"/>	
DOUBLE LAYER		<input type="checkbox"/>	
MULTILAYER		<input type="text" value="4"/> LAYERS (See Stackup)	
SILKSCREEN		<input type="checkbox"/> TOP	<input checked="" type="checkbox"/> BOT COLOR <input type="text" value="WHITE"/>
SOLDERMASK:			
IMAGEABLE		<input checked="" type="checkbox"/> TOP	<input checked="" type="checkbox"/> BOT COLOR <input type="text" value="RED"/>
OTHER		<input type="checkbox"/> TOP	<input type="checkbox"/> BOT
COATING COPPER			
SnPb SELECTIVE		<input type="checkbox"/>	
SnPb CONSOLIDATED		<input type="checkbox"/>	
NI-AU		<input type="checkbox"/> ELECTROLYTIC	
		<input checked="" type="checkbox"/> CHEMICAL	
OTHER		<input type="checkbox"/> : .	



ARTWORKS	LAYER N°	PCB	REV.	TYPE
TOP LAYER	1	PCB2445	0	311
INT. 2 LAYER	2	PCB2445	0	311
INT. 3 LAYER	3	PCB2445	0	311
INT. 4 LAYER	.	.	.	311
INT. 5 LAYER	.	.	.	311
INT. 6 LAYER	.	.	.	311
INT. 7 LAYER	.	.	.	311
INT. 8 LAYER	.	.	.	311
INT. 9 LAYER	.	.	.	311
BOTTOM LAYER	4	PCB2445	0	311
POWER_1	.	.	.	311
POWER_2	.	.	.	311
POWER_3	311
POWER_4	311
POWER_5	.	.	.	311
SOLDER MASK TOP	5	PCB2445	0	312
SOLDER MASK BOT	6	PCB2445	0	312
SILKSCREEN TOP	.	.	.	380
SILKSCREEN BOT	7	PCB2445	0	380
MILLING	8	PCB2445	0	313

LEGENDE DE PERCAGE / DRILL LEGEND

ALL UNITS ARE IN MILLIMETERS

FIGURE	DIAMETRE / HOLESIZE	PLATED	Qte / Qty
+	0,30 mm +0,10 -0,05	PLATED	77