

K32W041AM/A: High Performance, Secure and Low-Power MCU for Zigbee®, Thread™ and Bluetooth® LE 5.0 with High Tx Power Option

K32W041AM-A

Last Updated: Feb 19, 2025

The K32W0x portfolio is designed to power the next generation of ultra-low-current multiprotocol wireless IoT devices with support for Matter, IEEE 802.15.4 mesh network protocols Zigbee and Thread and Bluetooth Low Energy 5.0. The K32W041AM/A are compatible with the K32W061/41.

The K32W041AM and K32W041A family members support longer range and expanded memory optimized to facilitate home and building automation, smart lighting, smart locks, gateways, and routers.


The K32W041A/K32W041AM includes a 2.4 GHz Bluetooth Low Energy 5 (supporting eight simultaneous connections) compliant transceiver, a 2.4 GHz IEEE 802.15.4 compliant transceiver and a comprehensive mix of analog and digital peripherals. With 640 KB embedded Flash, 152 KB RAM memory, additional 1 MB data Flash with the K32W041AM, and support for Over-the-Air (OTA) updates, the K32W0x family provides scalability to address a variety of memory requirements. In addition, the K32W041AM/A extends the wireless radio output power to +15dBm.

These devices include a 10-channel PWM, two timers, one RTC/alarm timer, a Windowed Watchdog Timer (WWDT), two USARTs, two SPI interfaces, two I²C interfaces, a DMIC subsystem including a dual-channel PDM microphone interface with voice activity detector, one 12-bit ADC, temperature sensor and a comparator. The Arm Cortex-M4 is a 32-bit core operating at u to 48MHz that offers system enhancements such as low power consumption, enhanced debug features, and a high-level support of the block integration.

Devices across the K32W0x, JN18x and QN90x0 families are supported with common software stacks: Zigbee, OpenThread and Bluetooth LE.

For additional information and sample availability, contact your local Sales Office.

K32W041AM/A Block Diagram Block Diagram



View additional information for K32W041AM/A: High Performance, Secure and Low-Power MCU for Zigbee®, Thread[™] and Bluetooth® LE 5.0 with High Tx Power Option.

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2025 NXP B.V.