



# NTAG<sup>®</sup> 5 Link: NFC Forum-Compliant I<sup>2</sup>C Bridge for IoT on Demand

## NTAG5-LINK

Last Updated: Dec 17, 2024

Please check the new online [NFC Antenna Tool](#) for tag and reader devices.


NXP's NTAG 5 link lets designers of sensor-equipped systems add an NFC interface with a wired host interface that's configurable as an I<sup>2</sup>C controller/target, a Pulse Width Modulator (PWM), or a General-Purpose I/O (GPIO). Operating at 13.56 MHz, it is an NFC Forum-compliant contactless tag that can be read and written by an NFC-enabled device at close range and by an ISO/IEC 15693-enabled industrial reader over a longer range.

### Commitment to Longevity

NTP53x21G0J is ready to support your development today, tomorrow and beyond through its longevity program. The Product Longevity program ensures a stable supply of products for your embedded designs

[Learn more](#)

## NTAG 5 link block diagram Block Diagram



View additional information for [NTAG® 5 Link: NFC Forum-Compliant I<sup>2</sup>C Bridge for IoT on Demand](#).

**Note:** The information on this document is subject to change without notice.

**www.nxp.com**

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2025 NXP B.V.