



# Low-Ohmic Single-Pole Single-Throw Analog Switch

## NX3L1G384

### Archived


This page contains information on a product that is no longer manufactured (discontinued). Specifications and information herein are available for historical reference only.

Last Updated: Oct 14, 2023

The NX3L1G384 is a low-ohmic single-pole single-throw analog switch. It has two input/output terminals (Y and Z) and an active LOW enable input pin (E). When E is HIGH, the analog switch is turned off.

Schmitt trigger action at the enable input (E) makes the circuit tolerant to slower input rise and fall times. The NX3L1G384 allows signals with amplitude up to VCC to be transmitted from Y to Z; or from Z to Y. Its low ON resistance ( $0.5\ \Omega$ ) and flatness ( $0.13\ \Omega$ ) ensures minimal attenuation and distortion of transmitted signals.

## Block diagram: NX3L1G384GM, NX3L1G384GW, NX3V1G384GM, NX3V1G384GW Block Diagram



View additional information for [Low-Ohmic Single-Pole Single-Throw Analog Switch](#).

**Note:** The information on this document is subject to change without notice.

---

### **www.nxp.com**

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2025 NXP B.V.