

Multimedia Applications Processors - Connectivity, Arm11™ Core

i.MX353

Last Updated: Mar 4, 2025

NXP's Arm11[™]-based i.MX353 multimedia applications processors is targeted for consumer and industrial applications. To reduce the BOM costs it is packed with connectivity options including UARTs, SPIs, Ethernet, two Controller Area, Network (CAN) modules, two USB ports with integrated PHYs, ESAI and three MMC/SD/SDIO ports. The i.MX353 has the ability to connect to external wireless modules via a USB or SDIO port and supports external storage via CE-ATA or PATA. Support for cost-effective memory options like DDR2 and multi-level cell NAND reduce system costs and provide the design engineer great flexibility.

The i.MX353 is supported by companion NXP power management ICs (PMIC), MC13892 and MMPF0100.



RTC

GPIO

PATA

CE-ATA

i.MX353 Multimedia Applications Processor Block Diagram Block Diagram

View additional information for Multimedia Applications Processors - Connectivity, Arm11™ Core.

SLC NAND

MLC NAND

Inherited from i.MX31

Note: The information on this document is subject to change without notice.

Blending

Display Ctrl

New or enhanced from i.MX31

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2025 NXP B.V.