

AN11215

UCODE G2i PCB Antenna Reference Designs

Rev. 1.1 — 5 June 2013
235011

Application note
COMPANY PUBLIC

Document information

Info	Content
Keywords	UCODE EPC Gen2, G2i, Antenna Reference Design, PCB Antenna Design
Abstract	This application note describes three antenna reference designs for the UCODE G2i IC for implementation on a Printed Circuit Board (PCB).



Revision history

Rev	Date	Description
1.1	20130605	Update small antenna design
1.0	20120910	First initial release

Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

1. Introduction

The UCODE tag is compliant with the GS1 EPC™, Class-1 Generation-2 standard [1] and can be read by various RFID readers like fixed-mount-, gate-, tunnel- or handheld-readers. The read distance is dependent (amongst other things) on the type of the reader antenna and the design of the antenna on the PCB. Related to the design on the PCB the read distance for a large part depends on the size of the UHF antenna on the PCB. this document mainly describes the influence of the size of the antenna.

Real life applications may require different reading distance. The UCODE tag works with an antenna that is integrated on the PCB in the device. This application note describes three antenna reference designs with a large, medium and small antenna for a large, medium and small read distance. Conceptually the antennas utilize the ground planes of the PCB. The read performance is dependent upon the amount of copper in the ground plane. As a rule of thumb, more copper surface means more reading distance.

This application note provides measurement results with maximum and minimum amount of copper surfaces in the ground plane. For real life application the performance can be expected to be in the middle of the measured results. All measurements are done with "broadband" antenna designs (not specifically tuned for a certain geographic area).

The measurements in this application notes are optimized for optimal antenna orientations of both the reader and the tag antennas. All measurements are done in "free air", so without any loss due to some kind of shielding for example by the housing or other materials surrounding the PCB.

The measurement setup for the measurements in this application note is described in section 2. Section 3 described general design rules. Sections 4, 5 and 6 describe the antenna reference designs for the large, medium and small antennas respectively.


2. Measurement setup

This section describes the setup for the measurements in this application note.

2.1 Measurement setup

The minimum power measurements are carried out in a shielded chamber, according to the measurement setup described in the EPC global document “Tag Performance Parameters and Test Methods Version 1.1.1”.

The information gained from this measurement method is the minimal required power level at the label for powering the IC. This minimal power (P_{\min}) is measured for a defined frequency range from 840MHz to 960MHz.



2.2 Measurement in anechoic chamber

The read performance also depends on various environmental parameters. To eliminate all environmental factors as much as possible all measurements have taken place in an anechoic chamber.



Fig 2. Measurement Setup: Anechoic chamber

Note: The red arrow shows Tag position, PCB position horizontal (Fig 2) and vertical

Details of the measurement setup:

- **Reader antennas:** two bi-static horns with step attenuator
- **Reader antenna power:** 4W EIRP
- **Tag orientation:** PCB Horizontal (main beam of slotted antenna)
- **Distance between reader and PCB antenna:** 1 meter

3. General design rules

This section describes some general design rules for the antenna designs.

3.1 Antenna slot characteristics

The functional behavior of the PCB antenna is for a large part defined by the design of the antenna slot. The size of the slot defines the reading distance performance and the perimeter of the slot defines the antenna tuning.

3.2 Adaption for European and US bands

The operating frequency of an RFID system differs in Europe versus the US. In Europe the RFID systems must operate within the 865.6MHz - 867.6MHz band whereas in the US the RFID systems must operate within the 902MHz – 928MHz band.

For optimal operation the tag antennas need to be tuned to the correct frequency by varying the antenna slot perimeter values.

4. Large antenna reference design

This section describes the design of an antenna with the largest reading distance.

4.1 Antenna Geometry

The antenna is an integral part of the PCB. The brown part in [Fig 3](#) represents the ground plane (in this case the antenna fills the entire PCB).

The surface that is marked with the dotted line marks the minimum size of the ground plane.

In a real life application most of the ground plane surface will be occupied by electronic components and therefore the read/write performance may be less than the performance of this reference design antenna.




Fig 3. Large Antenna Reference Design


Details of the antenna design:

- Dimensions of the board: 80x45 mm
- Dimensions of the UHF antenna: 18 mm x 12.5 mm
- Antenna material: copper; thickness 35 μm ;
- Substrate material: FR4; thickness 1.5 mm;

4.2 Measurement results

Fig 4 shows the reading distance in meters over the frequency spectrum from 840MHz till 960MHz. The blue line shows the reading distance for maximum amount of copper surface in the ground plane and the brown line shows the reading distance for minimum amount of copper surface in the ground plane. For real life applications the performance can be expected to be in the middle of the measured results (Demo board).

Note: The mounting of electronic components could cause a change in the resonance frequency and therefore this could have a negative influence on the reading distance.



4.3 Demoboard




Fig 5. Demoboard with Large antenna

4.4 Demo board Measurement results




Fig 6. Measurement results Demoboard

5. Medium antenna reference design

This section describes the design of an antenna with a medium reading distance.

5.1 Antenna Geometry

The antenna is an integral part of the PCB. The brown part in [Fig 7](#) represents the ground plane. In a real life application most of the ground plane surface will be occupied by electronic components and therefore the read/write performance may be less than the performance of this reference design antenna.




Fig 7. Medium Antenna Reference Design

Details of the antenna design:

- Dimensions of the board: 80x45mm
- Dimensions of the UHF antenna: 12.5 mm x 10 mm
- Antenna material: copper; thickness 35 μm ;
- Substrate material: FR4; thickness 1.5 mm;

5.2 Measurement results

Fig 8 shows the reading distance in meters over the frequency spectrum from 840MHz till 960MHz. The blue line shows the reading distance for maximum amount of copper surface in the ground plane and the brown line shows the reading distance for minimum amount of copper surface in the ground plane.

For real life applications the performance can be expected to be in the middle of the measured results (Demo board).

Note: The mounting of electronic components could cause a change in the resonance frequency and therefore this could have a negative influence on the reading distance.




Fig 8. Medium design: Reading distance in meters




Fig 9. Medium design: Reading distance comparison in meters between G2iL and G2iM

5.3 Demoboard




Fig 10. Demoboard with Medium antenna

5.4 Demo board Measurement results




Fig 11. Measurement results Demoboard

6. Small antenna reference design

This section describes the design of an antenna with a small reading distance.

6.1 Antenna Geometry

The antenna is an integral part of the PCB. The yellow part in [Fig 12](#) represents the ground plane. In a real life application most of the ground plane surface will be occupied by electronic components and therefore the read/write performance may be less than the performance of this reference design antenna.




Fig 12. Small antenna design

Details of the antenna design:

- Dimensions of the board: 6x6mm
- Dimensions of the UHF antenna:
- Antenna material: copper; thickness 35 μm ;
- Substrate material: FR4; thickness 1.5 mm;

6.2 Demoboard




Fig 13. Demoboard with Small antenna

6.3 Demo board Measurement results




Fig 14. Measurement results Demoboard

7. References

- [1] EPC™ Radio-Frequency Identity Protocols, Class-1 Generation-2 UHF RFID, Protocol for Communications at 860MHz – 960MHz, Version 1.2.0; EPCglobal™ Inc. <http://www.nxp.com/redirect/gs1.org/gsm/kc/epcglobal/uhf1g2>
- [2] ISO/IEC 18000-1, *Information technology — Radio frequency identification for item management — Part 1: Reference architecture and definition of parameters to be standardized*
- [3] ISO/IEC 18000-6, *Information technology — Radio frequency identification for item management — Part 6: Parameters for air interface communications at 860MHz to 960MHz*
- [4] Data sheet, SL3S1203_1213; UCODE G2iL and G2iL+ (BLID 1788) http://www.nxp.com/documents/data_sheet/SL3S1203_1213.pdf
- [5] Data sheet: SL3S1003_1013; UCODE G2iM and G2iM+ (BLID 2012) http://www.nxp.com/documents/data_sheet/SL3S1003_1013.pdf
- [6] Application note: AN10940; FAQs on G2i http://www.nxp.com/restricted_documents/53420/AN10940.pdf
- [7] Application note: AN11237 UCODE G2iM+ Demoboard Documentation

8. Legal information

8.1 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

8.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine

whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer.

In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages.

Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

8.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are property of their respective owners.

UCODE— is a trademark of NXP B.V.

9. Contents

1.	Introduction	3
2.	Measurement setup.....	4
2.1	Measurement setup	4
2.2	Measurement in anechoic chamber	5
3.	General design rules.....	6
3.1	Antenna slot characteristics	6
3.2	Adaption for European and US bands.....	6
4.	Large antenna reference design	7
4.1	Antenna Geometry	7
4.2	Measurement results.....	8
4.3	Demoboard	9
4.4	Demo board Measurement results	9
5.	Medium antenna reference design	10
5.1	Antenna Geometry	10
5.2	Measurement results.....	11
5.3	Demoboard	12
5.4	Demo board Measurement results	12
6.	Small antenna reference design	13
6.1	Antenna Geometry	13
6.2	Demoboard	14
6.3	Demo board Measurement results	14
7.	References	15
8.	Legal information	16
8.1	Definitions	16
8.2	Disclaimers.....	16
8.3	Trademarks.....	16
9.	Contents.....	17

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.

© NXP B.V. 2013.

All rights reserved.

For more information, visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 5 June 2013
235011

Document identifier: AN11215