

MULTISENSORY ENABLEMENT KIT BASED ON i.MX 8QUADMAX APPLICATIONS PROCESSORS

The i.MX 8QuadMax Multisensory Enablement Kit (MEK) is ideal for safetycertifiable and efficient performance requirements.

The NXP i.MX 8QuadMax multisensory enablement kit (MEK) provides a comprehensive platform for quick evaluation and development of the Arm® Cortex® A72 + A53 Cortex-M4F based i.MX 8QuadMax and i.MX 8QuadPlus applications processors as well as the NXP PF8100 power management integrated circuit (PMIC) solution and sensors.

The MEK offers a high-level integration to support graphics, video, image processing, audio, and voice functions. Complete with highly optimized drivers and software, the i.MX 8QuadMax and and i.MX 8QuadPlus processors enable broad-based applications for the embedded industrial and automotive markets.

The kit includes an LVDS-to-HDMI adapter for simple out-of-the-box bring up. It has LPDDR4, eMMC, and QSPI memory options, a 10/100/1000 Ethernet port, USB 3.0 connectors and PCIe high-speed interfaces ideal for connected, high-performance embedded applications. For audio, video, and HMI evaluations, it brings out LVDS and MIPI-DSI connectors, and a headphone 3.5 mm audio jack.

The i.MX 8QuadMax MEK consists of a CPU board and an optional baseboard MCIMX8-8X-BB (ordered separately). The LVDS-to-HDMI adapter board is included with the MCIMX8QM-CPU. Extended audio features are supported by an audio card (IMX-AUD-IO) which is included with the baseboard.

TARGET APPLICATIONS

 Automotive—instrument cluster, infotainment, display audio, rear seat entertainment, smart antenna, vehicle-tovehicle (V2X), gateway and camera systems



- Industrial vehicle—avionics cockpit display, in-flight entertainment, train and heavy equipment human-machine interface (HMI)
- Advanced industrial HMI and control—PLC, I/O controller, home/building control
- Robotics—drone, mobile service robot
- Building control—fire and security panel, elevator control, HVAC control
- Healthcare—patient monitor
- Networking—specialty gateway, low-end video conference terminal
- Mobile payment—payment systems
- General-purpose HMI solutions
- Advanced vision for assistance, tracking and object detection
- Machine learning with high compute based systems
- Artifical intelligence analytics and scalable learning

GRAPHICS, VIDEO, AND AUDIO

The MEK has hardware accelerated video, graphics, and audio processing capabilities. The integrated video supports encode and decode for h.264 as well as decode for h.265. The graphics engine and display processor support rich

3D and 2D user interfaces while the Tensilica® HiFi 4 DSP supports audio pre- and post- processing, key word detection and speech recognition for hands-off interaction. Applications like infotainment, clusters, display audio, HMI, surveillance, and robotics can take advantage of the high level of multimedia integration.

HMI AND CONNECTIVITY

Today, HMI must respond accurately, and in miliseconds, to touch screen and gesture inputs. Connectivity is a must, demanding increasingly faster and more reliable wired and wireless capabilities associated with security to protect sensitive data and privacy. The i.MX 8QuadMax MEK provides capabilities for development of these key functionalities.

MX 8QUADMAX MEK CONTENTS

- CPU board (standalone)
- i.MX 8QuadXPlus MEK CPU board
- Power supply
- Quick Start Guide
- USB 3.0 Type C to Type A
- USB 2.0 Type A to Type Micro
- LVDS to HDMI adapter card
- Baseboard (ordered separately)
- i.MX 8/8X Baseboard
- i.MX 8/8X Audio board

SOFTWARE AND TOOLS

Hardware design files, software tools and board support packages (BSPs) for Linux®, Android™ and FreeRTOS are available from NXP to use as a reference for starting designs. QNX, Green Hills®, other commercial operating systems, and tools are also available from NXP's ecosystem partners. Additional information can be found at www.nxp.com/MCMX8QM-CPU.

i.MX 8QuadMax MEK Baseboard Features		
Part Number	Connectivity	Expansion Connector
MCIMX8-8X-BB	 1x I²C Auxiliary Connector 1x Tamper Head 1x Parallel CSI Connector 1x UART, 2x CAN 1x uUSB OTG connector 1x Audio In Connector, 1x Audio Out Connector 1x 10/100/1000 Ethernet connector Muxed w/ Audio port) 	Arduino Connector/ MikroBus Interface

i.MX 8QUADXPLUS MEK FEATURES

CPU Board		
Part Number: M	CIMX8QXP-CPU	
	NXP i.MX 8QuadXPlus	
Processor	2x Arm Cortex-A72 @ up to 1.6 GHz	
	4x Arm Cortex-A53 @ up to 1.2 GHz	
	• 1 GB L2 cache	
	2x Arm Cortex-M4 @ 266 MHz	
Power Management	NXP MMPF8100 PMIC	
Memory	3 GB LPDDR4 memory, x32	
	• 32 GB eMMC 5.0	
	64 MB Octal SPI Flash	
Display/Camera Connectors	2x MIPI-DSI / LVDS connectors	
	Camera MIPI-CSI	
Audio	Audio Codec	
Audio	Microphone and headphone jacks	
Connectivity	1x full-size SD/MMC card slot	
	2 x 1GB Ethernet with AVB	
	• 1x USB 3.0 Type C	
Debug	JTAG connector	
	Serial to USB connector	
Additional Feature OS Support	• 1× PCle 3.0	
	1× USB 3.0 with PHY	
	3× CAN/CAN-FD (If using i.MX 8 accessory board	
	MCIMX8-8X-BB)	
	2× 4-channel ADC converters	
	2× Enhanced Serial Audio Interface	
	• Linux	
	• Android	
	• FreeRTOS	
Expansion Connector	M.2 Connector (PCIe, USB, UART, I ² C and I ² S)	

There are a number of accessory boards that pair with the i.MX 8QM MEK CPU board and baseboard that include support for cameras and displays. Visit www.nxp.com/i.MX8-ACCESSORY-BOARDS to see the complete list.