



DSP56167

Advance Information 16-BIT DIGITAL SIGNAL PROCESSOR

The general purpose, programmable DSP56167 is an enhanced version of the DSP56166 with added features. Designed primarily for speech coding and digital communications, the DSP56167 has a built-in $\Sigma\Delta$ codec and Phase Lock Loop (PLL). This MPU-style DSP also contains memories and digital peripherals that provide a cost effective, high performance solution to many DSP applications. On-Chip Emulation (OnCE™) circuitry provides convenient and inexpensive debug facilities normally available only through expensive external hardware. This RAM-based DSP contains a 2 K × 16 Program RAM and a 4 K × 16 data RAM. The Central Processing Unit (CPU) consists of three execution units operating in parallel, allowing up to six operations to occur in an instruction cycle. This parallelism greatly increases the effective processing speed of the DSP56167. The MPU-style programming model and instruction set allow straightforward generation of efficient, compact code. The DSP56167 is a member of Motorola's DSP56100 family of 16-bit Digital Signal Processors (DSPs).




Figure 1 DSP56167 Block Diagram

AA0771

This document contains information on a new product. Specifications and information herein are subject to change without

DSP56167 FEATURES

- Digital Signal Processing Core
 - Up to 30 Million Instructions Per Second (MIPS) at 60 MHz with 33.3 ns instruction cycle
 - Single-cycle 16×16 -bit parallel Multiplier-Accumulator (MAC)
 - 2×40 -bit accumulators with extension byte
 - Fractional and integer arithmetic with support for multiprecision arithmetic
 - Highly parallel instruction set with unique DSP addressing modes
 - Nested hardware DO loops including infinite loops and DO zero loop
 - Two instruction LMS adaptive filter loop
 - Fast auto-return interrupts
 - Three external interrupt request pins
 - Three 16-bit internal data and three 16-bit internal address buses
 - Individual programmable wait states on the external bus for program, data, and peripheral memory spaces
 - Programmable absolute short addressing mode
 - Off-chip memory-mapped peripheral space with programmable access time and separate peripheral enable pin
 - Peripheral Address Generation Unit (PAGU)
 - On-chip memory-mapped peripheral registers
 - On-Chip Emulation (OnCE™) port for unobtrusive, processor speed-independent debugging with DR line static latch with Reset
- Memory
 - Modified Harvard architecture permits simultaneous accesses to program and data memories
 - $2 \text{ K} \times 16$ -bit on-chip Program RAM
 - $4 \text{ K} \times 16$ -bit on-chip data RAM
 - 64×16 -bit bootstrap ROM
 - External memory expansion with 16-bit address and data buses with static latches with Reset and software-controlled $\overline{\text{BG}}$ pull-down
 - Bootstrap loading from external byte-wide Program ROM, Host Interface, or 16-bit Synchronous Serial Interface (SSIO)

- Peripherals
 - Up to twenty-five General Purpose Input/Output (GPIO) pins, depending on which peripherals are enabled
 - Byte-wide Host Interface with Direct Memory Access (DMA) support (or up to fifteen Port B GPIO lines)
 - On-chip $\Sigma\Delta$ voice band codec, Analog-to-Digital (A/D) and Digital-to-Analog (D/A)
 - Internal voltage reference (1/2 of positive power supply) and split-voltage operation (with respect to the core)
 - No off-chip components required
 - 16-bit SSI support: two 4-pin ports (or up to eight Port C GPIO lines)
 - One 16-bit timer/event counter (or two Port C GPIO lines)
 - Double-buffered peripherals
 - Independent external chip enables \overline{BR} and \overline{PEREN} during Bus Master mode
 - Software-programmable, Phase Lock Loop-based (PLL) frequency synthesizer for the DSP core clock with a wide input frequency range (12.2 KHz to 60 MHz) that initializes to a preset low frequency operation during hardware reset
- Energy Efficient Design
 - Power-saving Wait and Stop modes
 - Fully static, HCMOS design allows operation from 60 MHz down to DC operating frequencies
 - 112-pin plastic Thin Quad Flat Pack (TQFP) surface-mount package

PRODUCT DOCUMENTATION

The three documents listed in the following table are required for a complete description of the DSP56167 and are necessary to design properly with the part. Documentation is available from one of the following locations (see back cover for detailed information):

- A local Motorola distributor
 - A Motorola semiconductor sales office
 - A Motorola Literature Distribution Center
- The World Wide Web (WWW) (the source for the latest information)

Table 1 DSP56167 Documentation

Name	Description	Order Number
DSP56100 Family Manual	Detailed description of the DSP56100 family processor core and instruction set	DSP56100FM/AD
DSP56167 User's Manual	Detailed functional description of the DSP56167 memory configuration, operation, and register programming	See note below
DSP56167 Technical Data	DSP56167 features list and physical, electrical, timing, and package specifications	DSP56167/D
<p>Note: The DSP56167 User's Manual is currently being developed and will not be available for general release until the end of the fourth quarter of 1996. The DSP56167 is a feature expanded, enhanced version of the DSP56166 and is entirely software compatible. Until the DSP56167 User's Manual is available, the user can refer to the <i>DSP56166 User's Manual</i>, order number DSP56166UM/AD for information common to both chips and Section 4 of the DSP56167 Technical Data sheet, order number DSP56167/D, for a description of the added features and enhanced capability of the DSP56167.</p>		

OnCE and Mfax are trademarks of Motorola, Inc.



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/Europe/Locations Not Listed:

Motorola Literature Distribution
P.O. Box 20912
Phoenix, Arizona 85036
1 (800) 441-2447 or
1 (602) 303-5454

Mfax™:

RMFAX0@email.sps.mot.com
TOUCHTONE (602) 244-6609

Asia/Pacific:

Motorola Semiconductors H.K. Ltd.
8B Tai Ping Industrial Park
51 Ting Kok Road
Tai Po, N.T., Hong Kong
852-2662928

Technical Resource Center:

1 (800) 521-6274

DSP Helpline

dsphelp@dsp.sps.mot.com

Japan:

Nippon Motorola Ltd.
Tatsumi-SPD-JLDC
6F Seibu-Butsuryu-Center
3-14-2 Tatsumi Koto-Ku
Tokyo 135, Japan
03-3521-8315

Internet:

<http://www.motorola-dsp.com>



**For More Information On This Product,
Go to: www.freescale.com**