



# i.MX RT1010 Crossover MCU with Arm® Cortex®-M7 Core Operating Up to 500 MHz

## i.MX-RT1010


Last Updated: Apr 11, 2024

i.MX RT1010 Crossover MCUs are based on the Arm® Cortex®-M7 core for real-time performance and high integration for Industrial and IoT applications.

The i.MX RT1010 CM7 operates at up to 500 MHz with 128 KB on-chip RAM that can be configured as TCM or general-purpose. The family offers various memory interfaces and a wide range of connectivity interfaces including UART, SPI, I<sup>2</sup>C, and USB. 80 LQFP packages included for low-cost PCB designs.

The i.MX RT1010 family is supported by the [MCUXpresso ecosystem](#), which includes an SDK, a choice of IDEs and secure provisioning and configuration tools to enable rapid development.

## i.MX RT1010 Crossover MCU Block Diagram



View additional information for [i.MX RT1010 Crossover MCU with Arm® Cortex®-M7 Core Operating Up to 500 MHz.](#)

**Note:** The information on this document is subject to change without notice.

**www.nxp.com**

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.