



i.MX RT1015 Crossover MCU with Arm® Cortex®-M7 Core Operating Up to 500 MHz

i.MX-RT1015

Last Updated: Jul 12, 2024

i.MX RT1015 Crossover MCUs are based on the Arm® Cortex®-M7 core for real-time performance and high integration and low cost Industrial and IoT applications.

The i.MX RT1015 CM7 operates at up to 500 MHz with 128 KB on-chip RAM that can be configured as TCM or general-purpose. The family offers various memory interfaces and a wide range of connectivity interfaces including UART, SPI, I²C and USB. 100 LQFP packages for low-cost PCB designs.

The i.MX RT1015 family is supported by the [MCUXpresso ecosystem](#), which includes an SDK, a choice of IDEs and secure provisioning and configuration tools to enable rapid development.

i.MX RT1015 Block Diagram Block Diagram



View additional information for [i.MX RT1015 Crossover MCU with Arm® Cortex®-M7 Core Operating Up to 500 MHz.](#)

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.