



Multimedia Applications Processors - Automotive Infotainment, High Resolution, High Color Display, High Performance, Low Power, Arm9™ Core

i.MX255


Last Updated: Nov 28, 2022

The i.MX255 applications processor is based on the fast, low power Arm926EJ-S™ CPU with advanced connectivity for automotive infotainment and applications that leverage auto-grade products.

For customers requiring high resolution and high color display the i.MX255 connects directly to high-resolution displays (up to SVGA) at high color depth (up to 18bpp) providing outstanding image quality. The addition of a Camera Interface (CMOS Sensor Interface) allows for video input acceptance, enabling support for applications such as, back-up cameras. Integration of DDR2, on-chip SRAM, and analog components like USB PHY, 12-bit ADC, and a resistive touchscreen controller reduces the Bill of Material (BOM) costs.

The need to connect too many different peripherals like Wi-Fi via SDIO or USB, Bluetooth via UART or SSI/I2S, and external storage via CE-ATA or PATA is addressed in the i.MX255 by supporting these interfaces and multiple other connectivity options, e.g. CAN, Smartcard Interface, 10/100 Ethernet with RMII support, and Enhanced Serial Audio Interface (ESAI).

i.MX255 Multimedia Applications Processor Block Diagram Block Diagram



View additional information for [Multimedia Applications Processors - Automotive Infotainment, High Resolution, High Color Display, High Performance, Low Power, Arm9™ Core.](#)

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2024 NXP B.V.