

MCUXpresso SDK Release Notes

Supporting LPCXpresso54608, LPCXpresso54618, and LPCXpresso54628



Contents

Chapter 1 Overview.....	3
Chapter 2 MCUXpresso SDK.....	4
Chapter 3 Development tools.....	5
Chapter 4 Supported development systems.....	6
Chapter 5 Release contents.....	7
Chapter 6 MCUXpresso SDK release package.....	9
Chapter 7 MISRA compliance.....	12
Chapter 8 Known issues.....	14

Chapter 1

Overview

The MCUXpresso Software Development Kit (SDK) is a collection of software enablement for Microcontrollers that includes peripheral drivers, high-level stacks including FatFs, USB, lwIP, other middleware packages, and integrated RTOS support for FreeRTOS™ OS. In addition to the base enablement, the MCUXpresso SDK is augmented with demo applications and driver example projects, and API documentation to help the customers quickly leverage the support of the MCUXpresso SDK.

For more details about MCUXpresso SDK, see the MCUXpresso SDK homepage [MCUXpresso-SDK: Software Development Kit](#).

NOTE

See the attached Change Logs section at the end of this document to reference the device-specific driver logs, middleware logs, and RTOS log.

Chapter 2

MCUXpresso SDK

As part of the MCUXpresso software and tools, MCUXpresso SDK is the evolution of Kinetis SDK v2.x.x, includes support for both LPC and i.MX System-on-Chips (SoC). The same drivers, APIs, and middleware are still available with support for Kinetis, LPC, and i.MX silicon. The MCUXpresso SDK adds support for the MCUXpresso IDE, an Eclipse-based toolchain that works with all MCUXpresso SDKs. Easily import your SDK into the new toolchain to have access to all of the available components, examples, and demos for your target silicon. In addition to the MCUXpresso IDE, support for the MCUXpresso Config Tools allows for easy cloning of existing SDK examples and demos, allowing users to easily leverage the existing software examples provided by the SDK for their own projects.

NOTE

In order to maintain compatibility with legacy Freescale code, the filenames and source code in MCUXpresso SDK containing the legacy Freescale prefix 'FSL' has been left as is. The 'FSL' prefix has been redefined as the NXP Foundation Software Library.

Chapter 3

Development tools

The MCUXpresso SDK was compiled and tested with these development tools:

- IAR Embedded Workbench for Arm version 8.32.3
- MDK-Arm Microcontroller Development Kit (Keil)[®] 5.27
- Makefiles support with GCC revision 8-2018-q4-major GCC8 from Arm Embedded
- MCUXpresso IDE v11.0.0

Chapter 4

Supported development systems

This release supports boards and devices listed in this table. Boards and devices in boldface were tested in this release:

Table 1. Supported MCU devices and development boards

Development boards	MCU devices
LPCXpresso54608, LPCXpresso54628, LPCXpresso54618	LPC54605J256ET180, LPC54605J512ET180, LPC54606J256ET180, LPC54606J512BD208, LPC54607J256ET180, LPC54607J512ET180, LPC54607J256BD208, LPC54608J512ET180 , LPC54628J512ET180, LPC54616J256ET180, LPC54616J512BD208, LPC54608J512BD208, LPC54618J512ET180 , LPC54618J512BD208, LPC54605J512BD100, LPC54605J256ET100, LPC54605J512ET100, LPC54605J256BD100, LPC54606J256ET100, LPC54606J512ET100, LPC54606J256BD100, LPC54606J512BD100

Chapter 5

Release contents

This table provides an overview of the MCUXpresso SDK release package contents and locations.

Table 2. Release contents

Deliverable	Location
Boards	<install_dir>/boards
TinyCBOR	<install_dir>/rtos/amazon-freertos/lib/third_party/tinycbor
Qualcomm WiFi	<install_dir>/middleware/wifi_qca
Demo applications	<install_dir>/boards/<board_name>/demo_apps
USB demo applications	<install_dir>/boards/<board_name>/usb_examples
lwIP demo applications	<install_dir>/boards/<board_name>/lwip_examples
Driver examples	<install_dir>/boards/<board_name>/driver_examples
Cortex Microcontroller Software Interface Standard (CMSIS) driver examples	<install_dir>/boards/<board_name>/cmsis_driver_examples
FatFS examples	<install_dir>/boards/<board_name>/fatfs_examples
emWin examples	<install_dir>/boards/<board_name>/emwin_examples
Component examples	<install_dir>/boards/<board_name>/component_examples
RTOS examples	<install_dir>/boards/<board_name>/rtos_examples
Qualcomm WiFi stack examples	<install_dir>/boards/<board_name>/wifi_qca_examples
Documentation	<install_dir>/docs
USB Documentation	<install_dir>/docs/usb
lwIP Documentation	<install_dir>/docs/lwip
Middleware	<install_dir>/middleware
lwIP stack	<install_dir>/middleware/lwip
FatFS stack	<install_dir>/middleware/fatfs
USB stack	<install_dir>/middleware/usb
Driver, SoC header files, extension header files and feature header files, utilities	<install_dir>/devices/<device_name>
CMSIS Arm Cortex [®] -M header files, DSP library source	<install_dir>/CMSIS
Peripheral Drivers	<install_dir>/devices/<device_name>/drivers
CMSIS drivers	<install_dir>/devices/<device_name>/cmsis_drivers
Utilities such as debug console	<install_dir>/devices/<device_name>/utilities
RTOS Kernel Code	<install_dir>/rtos
Tools	<install_dir>/tools

Table continues on the next page...

Table 2. Release contents (continued)

gradle	<install_dir>/boards/<board>/aws_examples/ remote_control_android/gradle, boards/<board>/ aws_examples/led_wifi_android/gradle, boards/<board>/ aws_examples/device_configuration_android/gradle
FNET	<install_dir>/boards/<board>/aws_examples/ device_configuration_enet/fnet_mdns

Chapter 6

MCUXpresso SDK release package

The MCUXpresso SDK release package contents are aligned with the silicon subfamily it supports. This includes the boards, CMSIS, devices, documentation, middleware, and RTOS support.

6.1 Device support

The device folder contains all available software enablement for the specific System-on-Chip (SoC) subfamily. This folder includes clock-specific implementation, device register header file, device register feature header file, CMSIS derived device SVD, and the system configuration source files. Included with the standard SoC support are folders containing peripheral drivers, toolchain support, and a simple debug console.

The device-specific header files provide a direct access to the MCU peripheral registers. The device header file provides an overall SoC memory mapped register definition. In addition to the overall device memory mapped header file, the MCUXpresso SDK also includes the feature header file for each peripheral instantiated on the SoC.

The toolchain folder contains the startup code and linker files for each supported toolchain. The startup code is a CMSIScompliant startup that efficiently transfers the code execution to the main() function.

6.1.1 Board support

The boards folder provides the board-specific demo applications, driver examples, RTOS, and middleware examples.

6.1.2 Demo applications and other examples

The demo applications demonstrate the usage of the peripheral drivers to achieve a system level solution. Each demo application contains a readme file that describes the operation of the demo and required setup steps.

The driver examples demonstrate the capabilities of the peripheral drivers. Each example implements a common use case to help demonstrate the driver functionality.

6.2 Middleware

6.2.1 USB stack

See the *MCUXpresso SDK USB Stack User's Guide* (document MCUXSDKUSBSUG) for more information.

6.2.1.1 Peripheral devices tested with USB Host stack

This table provides a list of USB devices tested with the USB Host stack.

Table 3. Peripheral devices

Device type	Device
-------------	--------

Table continues on the next page...

Table 3. Peripheral devices (continued)

USB HUB	BELKIN F5U233 BELKIN F5U304 BELKIN F5U307 BELKIN F4U040 UNITEK Y-2151 Z-TEK ZK032A HYUNDAI HY-HB608
USB flash drive	ADATA C008 32 GB ADATA S102 8 G ADATA S102 16 G Verbatim STORE N GO USB Device 8 G Kingston DataTraveler DT101 G2 SanDisk Cruzer Blade 8 GB Unisplendour 1 G Imation 2 GB V-mux 2 GB Sanmina-SCI 128 M Corporate Express 1 G TOSHIBA THUHYBS-008G 8 G Transcend JF700 8 G Netac U903 16 G SSK SFD205 8 GB Rex 4 GB SAMSUNG USB3.0 16GB
USB card reader/adapter	SSK TF adapter Kawau Multi Card Reader Kawau TF adapter Kawau SDHC card

Table continues on the next page...

Table 3. Peripheral devices (continued)

USB Mouse	DELL MS111-P DELL M066U0A DELL MUAVDEL8 TARGUS AMU76AP DELL MD56U0 DELL MS111-T RAPOO M110
USB Keyboard	DELL SK8135 DELL SK8115

6.2.2 TCP/IP stack

The lwIP TCP/IP stack is pre-integrated with MCUXpresso SDK and runs on top of the MCUXpresso SDK Ethernet driver with Ethernet-capable devices/boards. For details, see the *lwIP TCP/IP Stack and MCUXpresso SDK Integration User's Guide* (document MCUXSDKLWIPUG).

6.2.3 File system

The FatFs file system is integrated with MCUXpresso SDK and can be used to access either the SD card or the USB memory stick when the SD card driver or the USB Mass Storage Device class implementation is used.

6.2.4 RTOS

The MCUXpresso SDK is integrated with FreeRTOS OS.

6.2.5 CMSIS

The MCUXpresso SDK is shipped with the standard CMSIS development pack, including the prebuilt libraries.

6.2.6 emWin

The MCUXpresso SDK is pre-integrated with the SEGGER emWin GUIBuilder.

6.2.7 Other middleware

Optional middleware packages can be included in the release based on the user selection. See *<install_dir>/SW-Content-Register.txt* for a list of components and associated licenses.

Chapter 7

MISRA compliance

All MCUXpresso SDK drivers and USB stack comply to MISRA 2012 rules with the following exceptions.

Table 4. MISRA exceptions

Exception Rules	Description
Rule 5.1	External identifiers shall be distinct.
Rule 5.4	Macro identifiers shall be distinct.
Rule 21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.
Rule 21.2	A reserved identifier or macro name shall not be declared.
Directive 4.4	Sections of code should not be "commented out".
Directive 4.5	Identifiers in the same name space with overlapping visibility should be typographically unambiguous.
Directive 4.6	Typedefs that indicate size and signedness should be used in place of the basic numerical types.
Directive 4.8	If a pointer to a structure or union is never dereferenced within a translation unit, then the implementation of the object should be hidden.
Directive 4.9	A function should be used in preference to a function-like macro where they are interchangeable.
Directive 4.13	Functions which are designed to provide operations on a resource should be called in an appropriate sequence.
Rule 1.2	Language extensions should not be used.
Rule 2.3	A project should not contain unused type declarations.
Rule 2.4	A project should not contain unused tag declarations.
Rule 2.5	A project should not contain unused macro declarations.
Rule 2.6	A function should not contain unused label declarations.
Rule 2.7	There should be no unused parameters in functions.
Rule 4.2	Trigraphs should not be used.
Rule 5.9	Identifiers that define objects or functions with internal linkage should be unique.
Rule 8.7	Functions and objects should not be defined with external linkage if they are referenced in only one translation unit.
Rule 8.9	An object should be defined at block scope if its identifier only appears in a single function.
Rule 8.11	When an array with external linkage is declared, its size should be explicitly specified.

Table continues on the next page...

Table 4. MISRA exceptions (continued)

Rule 8.13	A pointer should point to a const-qualified type whenever possible.
Rule 10.5	The value of an expression should not be cast to an inappropriate essential type.
Rule 11.4	A conversion should not be performed between a pointer to object and an integer type.
Rule 11.5	A conversion should not be performed from pointer to void into pointer to object.
Rule 12.1	The precedence of operators within expressions should be made explicit.
Rule 12.3	The comma operator should not be used.
Rule 12.4	Evaluation of constant expressions should not lead to unsigned integer wrap-around.
Rule 13.3	A full expression containing an increment (++) or decrement (--) operator should have no other potential side effects other than that caused by the increment or decrement operator.
Rule 15.4	There should be no more than one break or go to statement used to terminate any iteration statement.
Rule 17.5	The function argument corresponding to a parameter declared to have an array type shall have an appropriate number of elements.
Rule 17.8	A function parameter should not be modified.
Rule 19.2	The union keyword should not be used.
Rule 20.1	#include directives should only be preceded by preprocessor directives or comments.
Rule 20.10	The #and ## preprocessor operators should not be used.
Rule 21.12	The exception handling features of <fenv.h> should not be used. .

Chapter 8

Known issues

8.1 Maximum file path length in Windows 7[®] operating system

Windows 7 operating system imposes a 260 character maximum length for file paths. When installing the MCUXpresso SDK, place it in a directory close to the root to prevent file paths from exceeding the maximum character length specified by the Windows operating system. The recommended location is the `C:\nxp` folder.

8.2 USB HUB power supply

The external power supply of the USB HUB must be provided before it can be used. The development board power is not enough to supply multi-level USB HUBs and connected devices. Therefore, the external USB HUB that is connected to the development board should have its own power supply.

8.3 USBFS controller issue

Because of the USBFS controller design issues, the USB host suspend/resume demos (`usb_suspend_resume_host_hid_mouse`) of the full speed controller do not support the low speed device directly.

8.4 USB high-speed interrupt endpoint issue

If the user wants to use a high-speed interrupt endpoint, the maximum packet size should be 512 bytes.

8.5 Create new project without board template

The following components should be selected at the same time when creating a new project without using a board template, including `serial_manager`, `serial_manager_uart`, `debug_console`, and one UART adapter (`lpuart_adapter` for LPUART IP, `uart_adapter` for UART IP, `lpsci_adapter` for LPSCI IP, etc).

8.6 New Project Wizard compile failure

The following components request the user to manually select other components that they depend on to pass the compile. These components depend on several components, and the New Project Wizard (NPW) is not able to decide which one is needed by the user.

NOTE

"xxx" means core variants like `cm0plus`, `cm33`, `cm4`, `cm33_nodsp`.

Components: `Assert`, `assert_cm0plus`, `assert_xxx`, `assert_lite`, `baremetal`, `button`, `codec_i2c`, `codec_i2c_xxx`, `debug_console`, `debug_console_xxx`, `debug_console_lite`, `dialog7212`, `led`, `misc_utilities`, `panic`, `serial_manager`, `serial_manager_xxx`,

serial_manager_swo, serial_manager_swo_xxx, serial_manager_uart, serial_manager_uart_xxx, serial_manager_usb_cdc, serial_manager_usb_cdc_xxx, sgtl_adapter, sgtl5000, shell, shell_xxx, timer_manager, wm8904, wm8904_xxx, wm8904_adapter, wm8904_adapter_xxx, wm8960, wm8960_adapter, xip_device.

MCUXpresso SDK Release Notes Supporting LPCXpresso54608, LPCXpresso54618, and LPCXpresso54S618

Change Logs

Contents

Driver Change Log	1
ADC	1
CRC	1
CTIMER	1
COMMON	2
DMA	2
DMIC	3
EEPROM	4
EMC	4
ENET	5
FLASHIAP	5
FLEXCOMM	5
I2C	6
I2S	6
SPI	7
USART	7
FMC	8
FMEAS	8
GINT	8
GPIO	8
INPUTMUX	9

Contents

Title	Page Number
IOCON	9
LCDC	9
MCAN	10
MRT	10
PDB	10
PINT	11
RIT	11
RNG	12
RTC	12
SCTIMER	12
SDIF	12
SPI Flash Interface	14
SYSCON	14
UTICK	14
WWDT	14
CLOCK	15
POWER	16
RESET	16
Middleware Change Log	17
emWin library	17
FatFs for MCUXpresso SDK	17
lwIP for MCUXpresso SDK	17
SDMMC	18
SDIO	21
SDSPI	22

Contents

Title	Page Number
USB stack for MCUXpresso SDK	22
RTOS Change Log	27
FreeRTOS for MCUXpresso SDK.	27

1 Driver Change Log

ADC

The current ADC driver version is 2.3.1.

- 2.3.1
 - Bug fix:
 - * Avoided write ADC STARTUP register in ADC_Init().
 - * Fixed coverity zero divider error in ADC_DoSelfCalibration().
- 2.3.0
 - Updated "ADC_Init()" "ADC_GetChannelConversionResult()" API and "adc_resolution_t" structure to match QN9090.
 - Added "ADC_EnableTemperatureSensor" API.
- 2.2.1
 - Improvement:
 - * Added a brief delay in uSec after ADC calibration start.
- 2.2.0
 - Updated "ADC_DoSelfCalibration" API and "adc_config_t" structure to match LPC845.
- 2.1.0
 - Renamed "ADC_EnableShresholdCompareInterrupt" to "ADC_EnableThresholdCompareInterrupt".
- 2.0.0
 - Initial version.

CRC

The current CRC driver version is 2.0.1.

- 2.0.1
 - Fixed KPSDK-13362. MDK compiler issue when writing to WR_DATA with -O3 optimize for time.
- 2.0.0
 - Initial version.

CTIMER

The current CTimer driver version is 2.0.2.

- 2.0.2
 - Added new API "CTIMER_GetTimerCountValue" to get the current timer count value.
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
 - Added new feature macro to update the API of CTimer driver for lpc8n04.

- 2.0.1
 - API Interface Change Added CTIMER_SetupPwmPeriod and CTIMER_UpdatePwmPulse-Period API. These two APIs can set up the right PWM with high resolution.
- 2.0.0
 - Initial version.

COMMON

The current COMMON driver version is 2.1.0.

- 2.1.0
 - New features:
 - * Added IRQ operation for XCC toolchain.
 - * Added group IDs for newly supported drivers.
- 2.0.2
 - MISRA C-2012 issue fixed.
 - * Fixed rule contain: rule-10.4.
- 2.0.1
 - Removed the implementation of LPC8XX Enable/DisableDeepSleepIRQ() function.
 - Added new feature macro switch "FSL_FEATURE_HAS_NO_NONCACHEABLE_SECTION" for specific SoCs which have no noncacheable sections, that helps avoid an unnecessary complex in link file and the startup file.
 - Updated the align(x) to **attribute**(aligned(x)) to support MDK v6 armclang compiler.
- 2.0.0
 - Initial version.

DMA

The current DMA driver version is 2.3.0.

- 2.3.0
 - Bug fix:
 - * Removed DMA_HandleIRQ prototype definition from header file.
 - * Added DMA_IRQHandle prototype definition in header file.
- 2.2.5
 - Improvements:
 - * Added new API DMA_SetupChannelDescriptor to support configure wrap descriptor.
 - * Added wrap support in function DMA_SubmitChannelTransfer.
- 2.2.4
 - Bug fix:
 - * Fixed the macro DMA_CHANNEL_CFER use wrong parameter to calculate DSTINC issue.
- 2.2.3
 - Bug fix:

- * Improved DMA driver Deinit function for correct logic order.
- Improvement:
 - * Added API DMA_SubmitChannelTransferParameter to support create head descriptor directly.
 - * Added API DMA_SubmitChannelDescriptor to support ping pong transfer.
 - * Added macro DMA_ALLOCATE_HEAD_DESCRIPTOR/DMA_ALLOCATE_LINK_DESCRIPTOR to simplify DMA descriptor allocation.
- 2.2.2
 - Bug fix:
 - * Do not use software trigger when hardware trigger is enabled.
- 2.2.1
 - Bug fix:
 - * Fixed coverity issue.
- 2.2.0
 - Improvements:
 - * Changed API DMA_SetupDMADescriptor to non-static.
 - * Marked below API as deprecated. DMA_PrepareTransfer. DMA_Submit transfer.
 - * Added below new API: DMA_SetChannelConfig. DMA_PrepareChannelTransfer. DMA_InstallDescriptorMemory. DMA_SubmitChannelTransfer. DMA_SetChannelConfigValid. DMA_DoChannelSoftwareTrigger. DMA_LoadChannelTransferConfig.
- 2.0.1
 - Improvement:
 - * Added volatile for DMA descriptor member xfercfg to avoid optimization.
- 2.0.0
 - Initial version.

DMIC

The current DMIC driver version is 2.1.0.

- 2.1.0
 - New feature
 - * Added API DMIC_EnableChannelInterrupt/DMIC_EnableChannelDma to replace API DMIC_SetOperationMode.
 - * Added API DMIC_SetIOCFG and mark DMIC_ConfigIO as deprecated.
 - * Added API DMIC_EnableChannelSignExtend to support sign extend feature.
- 2.0.5
 - Improvements:
 - * Changed some parameters value of DMIC_FifoChannel API, such as enable, resetn, and trig_level. This is not possible for the current code logic, so it improves the DMIC_FifoChannel logic and fixes incorrect math logic.
- 2.0.4
 - Bug fix:
 - * Fixed DMIC DMA driver (ver2.0.3) that does not support call DMIC_TransferReceive-

DMA in DMA callback, which is supported before 2.0.3, but calling DMIC_Transfer-ReceiveDMA in callback is not recommended.

- 2.0.3
 - New features:
 - * Supported linked transfer in DMIC DMA driver.
 - * Added new API DMIC_EnableChannelFifo/DMIC_DoFifoReset/DMIC_InstallDMA-Descriptor.
- 2.0.2
 - New feature:
 - * Supports more channels in driver.
- 2.0.1
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
 - Initial version.

EEPROM

The current EEPROM driver version is 2.1.1.

- 2.1.1
 - Fixed coverity BAD_SHIFT issues.
 - Fixed coverity MISRA rule 10.1/10.3/10.4/10.8/17.7 issues.
 - Updated parameter type from int into uint32_t for EEPROM_Write().
- 2.1.0
 - Added new API to support write/read EEPROM and data check on LPC8N04.

2.0.0

- Initial version.

EMC

The current EMC driver version is 2.0.3.

- 2.0.3
 - Improvements:
 - * Used SDK_DelayAtLeastUs instead of for loop during the dynamic memory initialization.
- 2.0.3
 - Replaced deprecated enumerator CLOCK_GetFreq(kCLOCK_EMCClkFreq) with CLOCK_GetEmc-ClkFreq()
- 2.0.2
 - Added control macro to enable/disable the CLOCK code in current driver.
- 2.0.1
 - Added const for two BASE values.
- 2.0.0

- Initial version.

ENET

The current ENET driver version is 2.1.3.

- 2.1.3
 - In ENET_StartRxTx, updated to enable TX and RX at the same time to avoid issue where ENET module could not work under 10 M.
 - Changed to use CLOCK_GetCoreSysClkFreq() instead of SystemCoreClock to get accurate core clock.
- 2.1.2
 - Fixed ENET receive issue where it sometimes loses some unicast packets. The issue is caused by the program timing issue for writing MAC_ADDR_LOW and MAC_ADDR_HIGH.
- 2.1.1
 - Added control macro to enable/disable the CLOCK code in current driver.
- 2.1.0
 - Added two APIs to set the ENET to ACCPET or reject the multicast frames.
- 2.0.0
 - Initial version.

FLASHIAP

The current FLASHIAP driver version is 2.0.3.

- 2.0.3
 - The FLASHIAP driver is marked as deprecated and will be removed in next release. All of its APIs are moved to the IAP driver. The names of FLASHIAP's APIs are updated from FLASHIAP_XXX() to IAP_XXX().
- 2.0.2
 - Added the API for extended flash signature
- 2.0.1
 - Removed two incorrect commands.
- 2.0.0
 - Initial version.

FLEXCOMM

The current FLEXCOMM driver version is 2.0.1.

- 2.0.1
 - Added more IRQHandler code in drivers to adapt new devices.
- 2.0.0
 - Initial version.

I2C

The current I2C driver version is 2.0.6.

- 2.0.6
 - Fixed coverity issue of unchecked return value in I2C_RTOS_Transfer.
- 2.0.5
 - Bug fix:
 - * Fixed build warning caused by uninitialized variable.
- 2.0.4
 - Updated the "I2C_MasterSetBaudRate" API to support baudrate configuration for feature Q-N9090.
- 2.0.4
 - Updated the I2C_WATI_TIMEOUT macro to unified name I2C_RETRY_TIMES.
- 2.0.3
 - Unified component full name to FLEXCOMM I2C(DMA/FREERTOS) driver.
- 2.0.2
 - Improvements: In slave IRQ:
 1. Changed slave receive process to first set the I2C_SLVCTL_SLVCONTINUE_MASK to acknowledge the received data, then do data receive.
 2. Improved slave transmit process to set the I2C_SLVCTL_SLVCONTINUE_MASK immediately after write the data.
- 2.0.1
 - Improvements:
 - * Added I2C_WATI_TIMEOUT macro to allow user to specify the timeout times for waiting flags in functional API and blocking transfer API.
- 2.0.0
 - Initial version.

I2S

The current I2S driver version is 2.1.0.

- 2.1.0
 - Improvements:
 - * Added feature for the FLEXCOMM which supports I2S and has interconnection with DMIC.
 - * Used feature to control PDMDATA instead of I2S_CFG1_PDMDATA.
 - * Added member bytesPerFrame in i2s_dma_handle_t, used for DMA transfer width configure instead of use sizeof(uint32_t) hardcode.
 - * Used the macro provide by DMA driver to define the I2S DMA descriptor.
 - Bug fix:
 - * Fixed I2S DMA driver to always generate duplicate callback.
- 2.0.3
 - Added feature to remove configuration for second channel on LPC51U68.

- 2.0.2
 - Added ENABLE_IRQ handle after register I2S interrupt handle.
- 2.0.1
 - Unified component full name to FLEXCOMM I2S (DMA) driver.
- 2.0.0
 - Initial version.

SPI

The current SPI driver version is 2.0.4.

- 2.0.4
 - Bug fix:
 - * Fixed the bug of using read only mode in DMA transfer. In DMA transfer mode, if transfer->txData is NULL, code attempts to read data from the address of 0x0 for configuring the last frame.
- 2.0.3
 - Added "SPI_FIFO_DEPTH(base)" more definition.
- 2.0.2
 - Unified component full name to FLEXCOMM SPI(DMA/FREERTOS) driver.
- 2.0.1
 - Changed the data buffer from uint32_t to uint8_t which matches the real applications for SPI DMA driver.
 - Added dummy data setup API to allow users to configure the dummy data to be transferred.
 - Added new APIs for half-duplex transfer function, users can send and receive data by one API in polling/interrupt/DMA way, and users can choose either transmit first or receive first. Also, the PCS pin can be configured as assert status in transmission (between transmit and receive) by setting the isPcsAssertInTransfer to true.
- 2.0.0
 - Initial version.

USART

- The current USART driver version is 2.1.0.
- 2.1.0
 - New feature:
 - * Added features to allow users to configure the USART to synchronous transfer (master and slave) mode.
- 2.0.3
 - New feature:
 - * Added new APIs to allow users to enable the CTS which determines whether CTS is used for flow control.
- 2.0.2

- Bug fix:
 - * Fixed the bug where transfer abort APIs cannot disable the interrupts. The FIFOINTENS-ET register should not be used to disable the interrupts, instead using the FIFOINTENCLR register.
- 2.0.1
 - Unified component full name to FLEXCOMM USART (DMA/FREERTOS) driver.
- 2.0.0
 - Initial version.

FMC

The current FMC driver version is 2.0.1.

- 2.0.1
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
 - Removed the incorrect RESET code in FMC_Init API in current driver.
- 2.0.0
 - Initial version.

FMEAS

The current FMEAS driver version is 2.1.0.

- 2.1.0
 - Updated "FMEAS_GetFrequency", "FMEAS_StartMeasure", "FMEAS_IsMeasureComplete" API and add definition to match ASYNC_SYSCON.
- 2.0.0
 - Initial version ported from LPCOpen.

GINT

The current GINT driver version is 2.0.1.

- 2.0.1
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
 - Initial version.

GPIO

The current GPIO driver version is 2.1.3.

- 2.1.4

- Added API `GPIO_PortGetInterruptStatus` to retrieve interrupt status for whole port.
- Corrected typo in header file.
- 2.1.3
 - Updated "GPIO_PinInit" API. If it has `DIRCLR` and `DIRSET` registers, use them at set 1 or clean 0.
- 2.1.2:
 - Removed deprecated APIs.
- 2.1.1:
 - API interface changes:
 - * Refined naming of API while keep all original APIs, marking them as deprecated. Original API will be removed in next release. The mainin change is update API with prefix of `_PinXXX()` and `_PorortXXX`
- 2.1.0
 - Added GPIO initialize API.
- 2.0.0
 - Initial version.

INPUTMUX

The current INPUTMUX driver version is 2.0.0.

- 2.0.0
 - Initial version.

IOCON

The current IOCON driver version is 2.1.1.

- 2.1.1
 - Updated left shift format with mask value instead of a constant value to automatically adapt to all platforms.
- 2.1.0
 - Added a new `IOCON_PinMuxSet()` function with a feature `IOCON_ONE_DIMENSION` for LPC845MAX board.
- 2.0.0
 - Initial version.

LCDC

The current LCDC driver version is 2.0.1.

- 2.0.1
 - Added control macro to enable/disable the `RESET` and `CLOCK` code in current driver.
- 2.0.0

- Initial version.

MCAN

The current MCAN driver version is 2.1.0.

- 2.1.0
 - Fixed coverity issue FORWARD_NULL.
 - Fixed Clang issue.
 - Implemented feature for improved timing configuration.
 - Fixed legacy issue in the driver and change default bus data baud rate for CANFD.
- 2.0.3
 - Used memset to initialize the structure before using.
 - Added function definition comment in c file.
 - Updated source file license to SPDX BSD_3.
 - Capital mistake of Fifo and fifo.
 - Added call reset in LPC drivers after clock enable.
- 2.0.2
 - Picked MISRA fix in release 8 branch.
 - MISRA C 2012 fix regarding FlexCAN and MCAN address update.
 - implemented for delay/retry in MCAN driver.
- 2.0.1
 - LPC54608 chip does not support the FD feature, so added a feature macro for it.
- 2.0.0
 - Initial version.

MRT

The current MRT driver version is 2.0.1.

- 2.0.1
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
 - Initial version.

PDB

The current PDB driver version is 2.0.1.

- 2.0.1
 - Changed PDB register base array to const.
- 2.0.0
 - Initial version.

PINT

The current PINT driver version is 2.1.3.

- 2.1.3
 - Bug fix:
 - * Updated PINT_PinInterruptClrStatus to clear PINT interrupt status when the bit is asserted and check whether was triggered by edge-sensitive mode.
 - * Write 1 to IST corresponding bit will clear interrupt status only in edge-sensitive mode and will switch the active level for this pin in level-sensitive mode.
 - * Fixed MISRA c-2012 rule 10.1, rule 10.6, rule 10.7.
 - * Added FSL_FEATURE_SECPINT_NUMBER_OF_CONNECTED_OUTPUTS to distinguish IRQ relevant array definitions for SECPINT/PINT on lpc55s69 board.
 - * Fixed PINT driver c++ build error and remove index offset operation.
- 2.1.2
 - Improvement:
 - * Improved way of initialization for SECPINT/PINT in PINT_Init API.
- 2.1.1
 - Improvement:
 - * Enabled secure pint interrupt and add secure interrupt handle.
- 2.1.0
 - Added PINT_EnableCallbackByIndex/PINT_DisableCallbackByIndex APIs to enable/disable callback by index.
- 2.0.2
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.1
 - Bug fix:
 - * Updated PINT driver to clear interrupt only in Edge sensitive.
- 2.0.0
 - Initial version.

RIT

The current RIT driver version is 2.1.0.

- 2.1.0
 - Fixed issue for wrong implementation of clearing counter API in RIT driver.
- 2.0.2
 - Added control macro to enable/disable the CLOCK code in current driver.
- 2.0.1
 - Fixed incorrect comments of some APIs.
- 2.0.0
 - Initial version.

RNG

The current RNG driver version is 2.0.0.

- 2.0.0
 - Initial version.

RTC

The current RTC driver version is 2.0.0.

- 2.0.0
 - Initial version.

SCTIMER

The current SCTimer driver version is 2.1.0.

- 2.1.0
 - Bug fixes:
 - * Fixed issue where SCT application level Interrupt handler function is occupied by SCT driver.
 - * Fixed issue where wrong value for INSYNC field inside SCTIMER_Init function.
 - * Fixed issue to change Default value for INSYNC field inside SCTIMER_GetDefaultConfig.
- 2.0.1
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
- 2.0.0
 - Initial version.

SDIF

The current SDIF driver version is 2.0.11.

- 2.0.11
 - Improvements:
 - * Added API SDIF_GetEnabledInterruptStatus/SDIF_GetEnabledDMAInterruptStatus and used in SDIF_TransferHandleIRQ.
 - * Removed useless members interruptFlags/dmaInterruptFlags in the sdif_handle_t.
 - * Improved SDIF_SendCommand with return success directly when timeout is 0.
 - * Added timeout error check when sending update clock command in SDIF_SetCardClock.
 - * Removed START_CMD status polling for normal command sending in SDIF_TransferBlocking/SDIF_TransferNonBlocking.
 - * Disabled timeout parameter in function SDIF_SendCommand.
 - Bug fix:

- * Added delay cycle for the default speed mode(400 K and 25 M) to fix the timing issue when different AHB clock is configured.
- 2.0.10
 - Bug fix:
 - * Fixed API SDIF_EnableCardClock that cannot clear the clock enable bit issue.
- 2.0.9
- Bug fix:
 - Fixed MDK 66-D warning.
- 2.0.8
- New features:
 - Added control macro to enable/disable the RESET and CLOCK code in current driver.
 - Disabled useless interrupt while DMA is used.
 - Updated SDIF driver for one instance support two card.
- 2.0.7
- Bug fix:
 - Enlarged the timeout value to avoid a command conflict issue.
- 2.0.6
- Bug fix:
 - Removed assert(srcClock_Hz <= FSL_FEATURE_SDIF_MAX_SOURCE_CLOCK).
 - Used hardware reset instead of software reset during initialize.
- 2.0.5
- New features:
 - Added non-word aligned data address and DMA descriptor address transfer support. Once one of the above addresses is not aligned, switch to host transfer mode.
- Bug fix:
 - Fixed the DMA suspend during initialization issue.
 - Removed useless memset function call.
- 2.0.4
 - Added cardInserted/cardRemoved callback function.
 - Added host base address/user data parameter for all call back functions.
- 2.0.3
 - Improved Clock Delay macro to allow the user to redefine and remove useless delay for clock below 25 MHz.
- 2.0.2
 - Bug fix:
 - * Fixed the issue where the status flag cannot be cleared entirely after transfer complete.
- 2.0.1
 - New features:
 - * Improve interrupt transfer callback.
 - Bug fix:
 - * Added assert to limit the SDIF source clock below 52 MHz.
- 2.0.0
 - Initial version.

SPI Flash Interface

The current SPIFI driver version is 2.0.2.

- 2.0.2
 - Fixed the set command function issue. After the command set, there is no wait for the CMD flag, as it may be cleared by CS deassert.
- 2.0.1
 - Added API to read/write 1/2 Bytes data from/to SPIFI. This interface are useful for flash command, which only needs 1/2 Bytes data. The previous driver needed users to make sure the minimum length should be 4, which may have issues in some flash commands.
- 2.0.0
 - Initial version.

SYSCON

The current SYSCON driver version is 2.0.0.

- 2.0.0
 - Initial version.

UTICK

The current UTICK driver version is 2.0.2.

- 2.0.2
 - Added new feature definition macro to enable/disable power control in drivers for some devices have no power control function.
- 2.0.1
 - Added control macro to enable/disable the CLOCK code in current driver.
- 2.0.0
 - Initial version.

WWDT

The current WWDT driver version is 2.1.2.

- 2.1.2
 - Updated "WWDT_ClearStatusFlags" and "WWDT_GetStatusFlags" API to match QN9090. WDTOF is not set in case of WD reset. Get info from PMC instead.
- 2.1.1
 - Added new feature definition macro for devices have no LCOK control bit in MOD register.
 - Implemented delay/retry in WWDT driver
- 2.1.0
 - Added new parameter in configuration when initializing WWDT module, this parameter allows

the user to deliver the WWDT clock frequency, and this parameter must be set.

- 2.0.0
 - Initial version.

CLOCK

The current CLOCK driver version is 2.2.0.

- 2.2.0
 - New Feature:
 - * add new APIs including `CLOCK_GetEmcClkFreq` and `CLOCK_GetMCanClkFreq` to replace `CLOCK_GetFreq(kCLOCK_MCAN0)` and `CLOCK_GetFreq(kCLOCK_EMCC)`
- 2.1.0
 - New feature
 - * Adding new API `CLOCK_DelayAtLeastUs()` implemented by DWT to allow users set delay in unit of microsecond.
- 2.0.5
 - Bug Fix:
 - * Correct the return frequency of `CLOCK_GetFrgClkFreq`.
 - * Fix the bug in function `CLOCK_GetPllConfig()` to refine the cache feature.
 - * Fix C++ build errors in `CLOCK_GetClockAttachId()` and `CLOCK_AttachClk()`.
- 2.0.4
 - Bug Fix:
 - * Update the second clock source to Flexcomm from `fro_hf` to `fro_hf_div`.
- 2.0.3
 - Bug Fix:
 - * Fix attach incorrect `attach_id`.
- 2.0.2
 - New Feature:
 - * add get actual clock attach id api to allow users to obtain the actual clock source in target register.
 - Bug Fix:
 - * The attach clock and get actual clock attach id apis should check combination of two clock source.
 - Optimization:
 - * Make the judgement statments more clear.
 - * Strengthen the compatibility of clock attach id.
 - * Remove some unmeaningful definitions and add some useful ones to enhance readability.
- 2.0.1
 - some minor fixes.
- 2.0.0
 - initial version.

POWER

The current POWER driver version is 2.0.0.

- 2.0.0
 - initial version.

RESET

The current RESET driver version is 2.0.1.

- 2.0.1
 - Update component full_name to "Reset Driver".
- 2.0.0
 - initial version.

2 Middleware Change Log

emWin library

The current version of emWin is 5.48r.

FatFs for MCUXpresso SDK

The current version is FatFs R0.13b_rev0.

- R0.13b_rev0
 - Upgraded to version 0.13b
- R0.13a_rev0
 - Upgraded to version 0.13a. Added patch ff_13a_p1.diff.
- R0.12c_rev1
 - Added NAND disk support.
- R0.12c_rev0
 - Upgraded to version 0.12c and applied patches ff_12c_p1.diff and ff_12c_p2.diff.
- R0.12b_rev0
 - Upgraded to version 0.12b.
- R0.11a
 - Added glue functions for low-level drivers (SDHC, SDSPI, RAM, MMC). Modified diskio.c.
 - Added RTOS wrappers to make FatFs thread safe. Modified syscall.c.
 - Renamed ffconf.h to ffconf_template.h. Each application should contain its own ffconf.h.
 - Included ffconf.h into diskio.c to enable the selection of physical disk from ffconf.h by macro definition.
 - Conditional compilation of physical disk interfaces in diskio.c.

lwIP for MCUXpresso SDK

The current version of lwIP is based on lwIP 2.1.2 and lwIP-contrib 2.1.0.

- 2.1.2_rev2
 - Bug fixes:
 - * Fixed lwiperf_abort() in lwiperf.c to correctly close connections and free resources
- 2.1.2_rev1
 - New features:
 - * Ported lwIP 2.1.2 (2018-11-22, SHA-1: 159e31b689577dbf69cf0683bbaffbd71fa5ee10) to KSDK 2.0.0.
 - * Ported lwIP-contrib 2.1.0 (2018-09-24, SHA-1: 35b011d4cf4c4b480f8859c456587a884ec9d287) to KSDK 2.0.0.
- 2.0.3_rev1
 - New features:

- * Ported lwIP 2.0.3 (2017-09-15, SHA-1: 92f23d6ca0971a32f2085b9480e738d34174417b) to KSDK 2.0.0.
- 2.0.2_rev1
 - New features:
 - * Ported lwIP 2.0.2 (2017-03-13, SHA-1: c0862d60746e2d1ceae69af4c6f24e469570ecef) to KSDK 2.0.0.
- 2.0.0_rev3
 - New features:
 - * Ported lwIP 2.0.0 (2016-11-10, SHA-1: 216bf89491815029aa15463a18744afa04df58fe) to KSDK 2.0.0.
- 2.0.0_rev2
 - New features:
 - * Ported lwIP 2.0.0 RC2 (2016-08-08, SHA-1: b1dfd00f9233d124514a36a8c8606990016f2ad4) to KSDK 2.0.0.
- 2.0.0_rev1
 - New features:
 - * Ported lwIP 2.0.0 RC0 (2016-05-26) to KSDK 2.0.0.
 - * Changed lwIP bare-metal examples to use poll-driven approach instead of interrupt-driven one.
- 1.4.1_rev2
 - New features:
 - * Enabled critical sections in lwIP.
 - Bug fixes:
 - * Fixed default lwIP packet-buffer size to be able to accept a maximum size frame from the ENET driver.
 - * Fixed possible drop of multi-frame packets during transmission.
- 1.4.1_rev1
 - New features:
 - * Ported lwIP 1.4.1 to KSDK 2.0.0.

SDMMC

The current driver version is 2.2.11.

- 2.2.11
 - Bug fixes:
 - * Fixed NULL pointer dereference issue when calling function SDMMCHOST_Card-DetectInit in host adaptor layer.
 - * Fixed logical dead code issue in SDMMC_SwitchToVoltage function.
- 2.2.10
 - Bug fixes:
 - * Added NULL pointer check for USDHC FreeRTOS adaptor transfer complete. callback.
 - * Added event value check for all the FreeRTOS event to fix program hang when a card event occurs before created.

- 2.2.9
 - Improvements:
 - * Added NULL pointer check for sdmmhostcard_usr_param_t member CD in card detect callback to avoid memory corruption.
 - * Added card voltage switch function in sdmmhostcard_usr_param_t to allow application register card signal line voltage switch function.
 - Bug fixes:
 - * Fixed host FreeRTOS adaptor and polling adaptor, where they cannot detect card insert bug for USDHC.
 - * Fixed SDHC host layer build issue and typo issue.
- 2.2.8
 - Improvement:
 - * Updated SDMMC to support SDIO interrupt.
- 2.2.7
 - Bug fixes:
 - * Fixed MDK 66-D warning.
- 2.2.6
 - Improvements:
 - * Removed some SoC-specific header files from porting layer.
 - * Saved MMC OCR registers while sending CMD1 with argument 0.
 - Bug fixes:
 - * Added MMC_PowerOn function in which there is delay function after powerup SD Card. Otherwise, the card may init fail.
- 2.2.5
 - New features:
 - * Added SD_ReadStatus API to get 512-bit SD status.
 - * Added error log support in SD Card functions.
 - * Added SDMMC_ENABLE_SOFTWARE_TUNING to enable/disable software tuning. It is disabled by default.
 - * Added error procedure in the transfer function to improve stability.
 - * Removed deprecated GPIO API in host layer.
- 2.2.4
 - Bug fix:
 - * Fixed DDR mode data sequence miss issue, which is caused by NIBBLE_POS.
 - New features:
 - * Increased g_sdmmc 512 Bytes to improve performance when application uses a non-word align data buffer address.
 - * Used OCR access mode bits to determine the MMC Card high capacity flag.
 - * Enabled auto CMD12 for SD read/write.
 - * Disabled DDR mode frequency multiply by 2.
- 2.2.3
 - Bug fix:
 - * Added response check for send operation condition command. If not checked, the card may occasionally init fail.
- 2.2.2

- Moved set card detect priority operation before enable IRQ.
- 2.2.1
 - New features:
 - * Improved MMC Boot feature.
 - * Kept SD_Init/SDIO_Init function for forward compatibility.
- 2.2.0
 - New features:
 - * Separated the SD/MMC/SDIO init API to xxx_CardInit/xxx_HostInit.
 - * Allowed user register card detect callback, select card detect type, and determine the card detect timeout value.
 - * Allowed user register the power on/off function, and determine the power on/off delay time.
 - * SD_Init/SDIO_Init is deprecated in the next version.
 - * Added write complete wait operation for MMC_Write to fix command timeout issue.
- 2.1.6
 - Enhanced SD IO default driver strength.
- 2.1.5
 - Fixed coverity issue.
 - Fixed SD v1.x card write fail issue. It was caused by the block length set error.
- 2.1.4
 - Miscellaneous:
 - * Added Host reset function for card re-initialization.
 - * Added Host_ErrorRecovery function for host error recovery procedure.
 - * Added cache maintain operation
 - * Added HOST_CARD_INSERT_CD_LEVEL to improve compatibility.
 - Bug fix:
 - * Fixed card cannot detect dynamically.
- 2.1.3
 - Bug fix:
 - * Non high-speed sdc card init fail at switch to high speed.
 - Miscellaneous:
 - * Optimized tuning/mmc switch voltage/mmc select power class/mmc select timing function.
 - * Added strobe dll for mmc HS400 mode.
 - * Added Delay for SDCard power up.
- 2.1.2
 - New features:
 - * Added fsl_host.h to provide prototype to adapt different controller IPs(SDHC/SDIF).
 - * Added adaptor code in SDMMC/Port folder to adapt different host controller IPs with different transfer modes(interrupt/polling/freertos). Application includes a different adaptor code to make application more simple.
 - * Adaptor code provides HOST_Init/HOST_Deinit/CardInsertDetect. APIs to do host controller initialize and transfer function configuration. SDMMC card stack uses adaptor code inside stack to wait card insert and configure host when calling card init APIs (SD_Init/MMC_Init/SDIO_Init).

- * This change requires the user to include host adaptor code into the application. If not changed, link errors saying it cannot find the definition of HOST_Init/HOST_Deinit/CardInsertDetect appear.
- New features: Improved SDMMC to support SD v3.0 and eMMC v5.0.
- Bug fix:
 - * Fixed incorrect comparison between count and length in MMC_ReadBlocks/MMC_WriteBlocks.
- 2.1.1
 - Bug fix:
 - * Fixed the block range boundary error when transferring data to MMC card.
 - * Fixed the bit mask error in the SD card switch to high speed function.
 - Other changes:
 - * Added error code to indicate that SDHC ADMA1 transfer type is not supported yet.
 - * Optimized the SD card initialization function.
- 2.1.0
 - Bug fix:
 - * Changed callback mechanism when sending a command.
 - * Fixed low performance issue when transferring data.
 - Other changes:
 - * Changed the name of some error codes returned by internal function.
 - * Merged all host related attributes to one structure.
 - * Optimize the function of setting maximum data bus width for MMC card.

SDIO

The current driver version is 2.2.11.

- 2.2.11
 - Bug fix:
 - * Added check card async interrupt capability in function SDIO_GetCardCapability.
 - * Fixed OUT OF BOUNDS access in function SDIO_IO_Transfer.
- 2.2.10
 - Bug fix:
 - * Fixed SDIO card driver get wrong IO number when the card IO number is bigger than 2.
 - New feature:
 - * Added SDIO 3.0 support.
 - * Added API SDIO_IO_RW_Direct for direct read/write card register access.
- 2.2.9
 - Improvement:
 - * Added API SDIO_SetIOIRQHandler/SDIO_HandlePendingIOInterrupt to handle multi IO pending IRQ.
- 2.2.8
 - Improvement:
 - * Updates SDMMC to support SDIO interrupt.

- * Added API SDIO_GetPendingInterrupt to get the pending IO interrupt.
- 2.2.7
 - Bug fix:
 - * Fixed MDK 66-D warning.
- 2.2.6
 - New features:
 - * Added a unified transfer interface for SDIO.
 - Bug fix:
 - * Wrong pointer address used by SDMMCHOST_Init.
- 2.1.5
 - Bug fix:
 - * Improved SDIO card init sequence and added retry option for SDIO_SwitchToHighSpeed function.
- 2.1.4
 - Miscellaneous:
 - * Added Go_Idle function for SDIO card.
- 2.0.0
 - Initial version.

SDSPI

The current SDSPI driver version is 2.1.4.

- 2.1.4
 - Bug fix:
 - * Fixed MDK 66-D warning.
- 2.1.3
 - Improved SDSPI code size and performance.
- 2.0.0
 - Initial version.

USB stack for MCUXpresso SDK

The current version of USB stack is 2.2.0.

- 2.2.0
 - New features:
 - * Added device DFU support.
 - * Supports OM13790DOCK on LPCXpresso54018.
 - * Added multiple logical unit support in MSC class driver, updated usb_device_lba_information_struct_t to support this.
 - * Supports multiple transfers for host ISO on IP3516HS.
 - Bug fixes:
 - * Fixed device ip3511 prime data length than maxpacket size issue.

- * Initialized interval attribute in `usb_device_endpoint_struct_t/usb_device_endpoint_init_struct_t`.
- * Removed unnecessary header file in device CDC class driver, removed unnecessary `usb_echo`, and added `DEBUG` macro for necessary `usb_echo` in device CDC class driver.
- * Fixed device IP3511HS unfinished interrupt transfer missing issue.
- 2.1.0
 - New features:
 - * Added host RNDIS support. example: `lwip_dhcp_usb`
 - * Enabled USB 3.0 support on device stack.
 - * Power Delivery feature: Added OM13790HOST support. Added auto policy feature. Printed e-marked cable information.
- 2.0.1
 - Bug fixes:
 - * Fixed some USB issues: Fixed MSC CV test failed in MSC examples.
 - * Changed audio codec interfaces.
- 2.0.0
 - New features:
 - * PTN5110N support.
 - Bug fix:
 - * Added some comments, fixed some minor USB issues.
- 1.9.0
 - New features:
 - * Examples:
 - `usb_pd_alt_mode_dp_host`
- 1.8.2
 - Updated license.
- 1.8.1
 - Bug fix:
 - * Verified some hardware issues, support `aruba_flashless`.
- 1.8.0
 - New features:
 - * Examples:
 - `usb_device_composite_cdc_vcom_cdc_vcom`
 - `usb_device_composite_hid_audio_unified`
 - `usb_pd_sink_battery`
 - Changed `usb_pd_battery` to `usb_pd_charger_battery`.
- Bug fix:
 - Code clean up, removed some irrelevant code.
- 1.7.0
 - New features:
 - * USB PD stack support.
 - Examples:
 - * `usb_pd`

- * usb_pd_battery
 - * usb_pd_source_charger
- 1.6.3
 - Bug fix: -IP3511_HS driver control transfer sequence issue, enabled 3511 ip cv test.
- 1.6.2
 - New features:
 - * Multi instance support.
- 1.6.1
 - New features:
 - Changed the struct variable address method for device_video_virtual_camera and host_phdc_manager.
- 1.6.0
 - New features:
 - * Supported Device Charger Detect feature on usb_device_hid_mouse.
- 1.5.0
 - New features:
 - * Supported controllers
 - OHCI (Full Speed, Host mode)
 - IP3516 (High Speed, Host mode)
 - IP3511 (High Speed, Device mode)
 - * Examples:
 - usb_lpm_device_hid_mouse
 - usb_lpm_device_hid_mouse_lite
 - usb_lpm_host_hid_mouse
- 1.4.0
 - New features:
 - * Examples:
 - usb_device_hid_mouse/freertos_static
 - usb_suspend_resume_device_hid_mouse_lite
- 1.3.0
 - New features:
 - * Supported roles
 - OTG
 - * Supported classes
 - CDC RNDIS
 - * Examples
 - usb_otg_hid_mouse
 - usb_device_cdc_vnic
 - usb_suspend_resume_device_hid_mouse
 - usb_suspend_resume_host_hid_mouse
- 1.2.0
 - New features:
 - * Supported controllers
 - LPC IP3511 (Full Speed, Device mode)
- 1.1.0

- Bug fix:
 - * Fixed some issues in USB certification.
 - * Changed VID and Manufacturer string to NXP.
- New features:
 - * Supported classes
 - Pinter
 - * Examples:
 - usb_device_composite_cdc_msc_sdcard
 - usb_device_printer_virtual_plain_text
 - usb_host_printer_plain_text
- 1.0.1
 - Bug fix:
 - * Improved the efficiency of device audio speaker by changing the transfer mode from interrupt to DMA, thus providing the ability to eliminate the periodic noise.
- 1.0.0
 - New features:
 - * Supported roles
 - Device
 - Host
 - * Supported controllers:
 - KHCI (Full Speed)
 - EHCI (High Speed)
 - * Supported classes:
 - AUDIO
 - CCID
 - CDC
 - HID
 - MSC
 - PHDC
 - VIDEO
 - * Examples:
 - usb_device_audio_generator
 - usb_device_audio_speaker
 - usb_device_ccid_smart_card
 - usb_device_cdc_vcom
 - usb_device_cdc_vnic
 - usb_device_composite_cdc_msc
 - usb_device_composite_hid_audio
 - usb_device_composite_hid_mouse_hid_keyboard
 - usb_device_hid_generic
 - usb_device_hid_mouse
 - usb_device_msc_ramdisk
 - usb_device_msc_sdcard
 - usb_device_phdc_weightscale
 - usb_device_video_flexio_ov7670

- usb_device_video_virtual_camera
- usb_host_audio_speaker
- usb_host_cdc
- usb_host_hid_generic
- usb_host_hid_mouse
- usb_host_hid_mouse_keyboard
- usb_host_msd_command
- usb_host_msd_fatfs
- usb_host_phdc_manager
- usb_keyboard2mouse
- usb_pin_detect_hid_mouse

3 RTOS Change Log

FreeRTOS for MCUXpresso SDK.

The current version is Amazon-FreeRTOS 1.4.0 Original package is available at github.com/aws/amazon-freertos.

- 1.4.7_rev0
 - New features:
 - * Add optional allocation scheme heap_useNewlib.c by D. Nadler.
 - * Enable task aware debugging for cm33 platforms
 - * Move tickless implementation to application layer
 - Other changes:
 - * Fix other build warnings, errors
- 1.4.6_rev0
 - New features:
 - * Update support of CM33 port with Trustzone, MPU, FPU support
 - * Add support for AWS test for Cypress WiFi
 - * Use lwip netif api to avoid lwIP raw API calls outside of tcpip thread in aws_wifi.c
 - Other changes:
 - * Fix issues with mflash driver
 - * Fix other build warnings, errors
- 1.4.0_rev1
 - New features:
 - * Add implementation of vTaskEndScheduler for CM0 GCC port.
 - * Support for CM33, CM33F architectures based on CM3, CM4F ports
- 1.4.0_rev0
 - New features:
 - * Support for pkcs11 for several platforms, secure element host library under pkcs11/portable/nxp folder
 - * Lwip, wifi_qca support for secure_sockets in secure_sockets/portable/nxp folder
 - * Flash driver support for several platforms in third_party/mcu_vendor/nxp folder
 - * Generic support for aws_wifi under wifi/portable/nxp/common folder
 - Other changes:
 - * Fix several build warnings, errors

Updates applied to FreeRTOS kernel up to version 10.0.0 (up to Amazon - FreeRTOS merge). New kernel related changes will be described in section above as part of AWS package.

- 9.0.0_rev3
 - New features:
 - * Tickless idle mode support for Cortex-A7. Add fsl_tickless_epit.c and fsl_tickless_generic.h in portable/IAR/ARM_CA9 folder.
 - * Enabled float context saving in IAR for Cortex-A7. Added configUSE_TASK_FPU_SUPPORT macros. Modified port.c and portmacro.h in portable/IAR/ARM_CA9 folder.

- Other changes:
 - * Transformed ARM_CM core specific tickless low power support into generic form under freertos/Source/portable/low_power_tickless/.
- 9.0.0_rev2
 - New features:
 - * Enabled MCUXpresso thread aware debugging. Add freertos_tasks_c_additions.h and configINCLUDE_FREERTOS_TASK_C_ADDITIONS_H and configFRTOS_MEMORY_SCHEME macros.
- 9.0.0_rev1
 - New features:
 - * Enabled -fno optimization in GCC by adding **attribute((used))** for vTaskSwitchContext.
 - * Enabled KDS Task Aware Debugger. Apply FreeRTOS patch to enable configRECORD_STACK_HIGH_ADDRESS macro. Modified files are task.c and FreeRTOS.h.
- 9.0.0_rev0
 - New features:
 - * Example freertos_sem_static.
 - * Static allocation support RTOS driver wrappers.
 - Other changes:
 - * Tickless idle rework. Support for different timers is in separated files (fsl_tickless_systick.c, fsl_tickless_lptmr.c).
 - * Removed configuration option configSYSTICK_USE_LOW_POWER_TIMER. Low power timer is now selected by linking of appropriate file fsl_tickless_lptmr.c.
 - * Removed configOVERRIDE_DEFAULT_TICK_CONFIGURATION in RVDS port. Use of **attribute((weak))** is the preferred solution. Not same as `_weak!`
- 8.2.3
 - New features:
 - * Tickless idle mode support.
 - * Added template application for Kinetis Expert (KEx) tool (template_application).
 - Other changes:
 - * Folder structure reduction. Keep only Kinetis related parts.

How To Reach Us

Home Page:

nxp.com

Web Support:

nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

While NXP has implemented advanced security features, all products may be subject to unidentified vulnerabilities. Customers are responsible for the design and operation of their applications and products to reduce the effect of these vulnerabilities on customer's applications and products, and NXP accepts no liability for any vulnerability that is discovered. Customers should implement appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, I2C BUS, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC, MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, Altivec, C-5, CodeTEST, CodeWarrior, ColdFire, ColdFire+, C-Ware, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorIQ, QorIQ Qonverge, Ready Play, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platform in a Package, QUICC Engine, SMARTMOS, Tower, TurboLink, and UMEMS are trademarks of NXP B.V. All other product or service names are the property of their respective owners. AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, μ Vision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© NXP B.V. 2019.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 06/2019

Document identifier: MCUXSDKLPC546XRN

