

# AN10928

## Enhanced BOD function of LPC98x/97x

Rev. 01 — 9 April 2010

Application note

### Document information

Info	Content
<b>Keywords</b>	LPC98x, LPC97x, enhanced BOD, brownout detect
<b>Abstract</b>	This application note describes how to use enhanced BOD function in LPC98x/97x. Demo code is also provided.



## Revision history

Rev	Date	Description
01	20100409	Initial version.

## Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 1. Introduction

The brownout detect function determines if the power supply voltage drops below a certain level. The Enhanced BOD feature of the P89LPC98x/97x has three independent functions: BOD reset, BOD interrupt and BOD flash.

## 2. BOD flash

BOD flash is used for flash program/erase protection. BOD flash is always on, except in power-down or total power-down mode (PCON.1 = 1). It can not be disabled in software. BOD flash has only one trip voltage level at 2.4 V.

For the 2K/4K/8K bytes of on-chip flash, the BOD flash is tripped and flash erase/program is blocked when  $V_{DD}$  is lower than 2.4 V. The HVA bit in the FMCON register indicates the BOD flash occurred.

## 3. BOD reset and BOD interrupt

A BOD reset will cause a processor reset and it is always enabled, except in power-down or total power-down mode. It can not be disabled in software. The BOD interrupt will generate an interrupt and can be enabled or disabled in software.

The BOD reset and BOD interrupt each has six trip voltage levels. BOE0 to BOE2 (UCFG1[3:5]) are used as the trip point configuration bits of BOD reset. BOICFG0 to BOICFG2 in the BODCFG register are used as trip point configuration bits for the BOD interrupt. The BOD reset voltage should be lower than the BOD interrupt trip point. [Table 1](#) and [Table 2](#) give BOD trip point configuration.

**Table 1. BOD reset trip points configuration**

BOE2 (UCFG1.5)	BOE1 (UCFG1.4)	BOE0 (UCFG1.3)	BOD reset	
			Fall	Rise
0	0	0	Reserved	Reserved
0	0	1	Reserved	Reserved
0	1	0	2.25 V	2.4 V
0	1	1	2.55 V	2.7 V
1	0	0	2.85 V	3.0 V
1	0	1	3.15 V	3.3 V
1	1	0	3.85 V	4 V
1	1	1	4.05 V	4.2 V

**Table 2. BOD interrupt trip points configuration**

BOICFG2 (BODCFG.2)	BOICFG1 (BODCFG.1)	BOICFG0 (BODCFG.0)	BOD interrupt	
			Fall	Rise
0	0	0	Reserved	Reserved
0	0	1	Reserved	Reserved
0	1	0	2.55 V	2.7 V
0	1	1	2.85 V	3.0 V
1	0	0	3.0 V	3.15 V
1	0	1	3.45 V	3.6 V
1	1	0	4.15 V	4.3 V
1	1	1	4.35 V	4.5 V

After power-on reset, the value of BOICFG 2 to BOICFG 0 bits will be copied from UCFG1.5 to UCFG1.3. The factory preprogrammed value of the UCFG1 register is 0x53 as shown in [Table 3](#). In this case, the trip voltage level is 2.25 V (fall) and 2.4 V (rise) for the BOD reset and 2.55 V (fall) and 2.7 V (rise) for the BOD interrupt. Of course, it is possible to change the trip point of the BOD interrupt in software. When configuring the trip voltage of the BOD reset, make sure the operational supply voltage is high enough. Otherwise it will cause the processor to be reset continuously.

In power-down mode (PMOD1/PMOD0 = '10') or total power-down mode (PMOD1/PMOD0 = '11'), the circuitry for the Brownout Detection is disabled for lowest power consumption. When the PMOD1/PMOD0 bits are not equal to '10' or '11', BOD reset is always enabled and the BOD interrupt is enabled by setting BOI (PCON.4) bit. Please refer to [Table 4](#) for BOD reset and BOD interrupt configuration. For the BOF bit (RSTSRC.5), the BOD reset flag has a default value of '0' and is set when a BOD reset is tripped. For the BOIF bit (RSTSRC.6), the BOD interrupt flag default state is '0'; this bit is set when the BOD interrupt is tripped.

**Table 3. Flash user configuration byte 1 (UCFG1) bit allocation**

Bit	7	6	5	4	3	2	1	0
Symbol	CLKDBL	RPE	BOE2	BOE1	BOE0	FOSC2	FOSC1	FOSC0
Unprogrammed value	0	1	0	1	0	0	1	1

Table 4. BOD reset and BOD interrupt configuration

PMOD1/PMOD0 (PCON[1:0])	BOI (PCON.4)	EBO (IEN0.5)	EA (IEN0.7)	BOD reset	BOD interrupt
'10' (power-down) or '11' (total power- down)	X	X	X	N	N
'00' or '01' (normal or idle mode)	0	X	X	Y	N
	1	0	X	Y	N
		1	0	Y	N
		1	1	Y	Y

## 4. BOD demo

### 4.1 Demo introduction

This demo gives an example on how to use the enhanced BOD feature. The Keil MCB900 board with a LPC982 is used for this application note.

In the demo, the trip voltage is set to 2.25 V (fall) and 2.4 V (rise) for BOD reset and 2.55 V (fall) and 2.7 V (rise) for a BOD interrupt. While the LPC982 is running, the power supply is adjusted to lower than 2.55 V to trigger BOD interrupt. The ISR of the BOD interrupt will set the BOD\_flag and blink the LEDs. In the main function, BOD\_flag is polled. When it is set, the information of "BOD interrupt" will be output through UART0. The UART interface is configured as 9600 Hz baud rate, 8 bit data, no parity, and 1 stop bit.

The BOE2 to BOE0 bits (UCFG1.5 to 1.3) are set to '010'. The subroutine BOD\_Int\_Config() implements BOD interrupt initialization.

```

1      BODCFG = 0x02;    // set BODCFG = 0000 0010 bin: the BOD int voltage is
      2.55V fall and 2.7V rise
2      EA = 1;           // set Enable all interrupts
3      EBO = 1;          // set BOD enable
4      PCON |= 0x10;     // set BOD interrupt enable

```

The BOD interrupt ISR is implemented as below. BOD\_flag is used to indicate the BOD interrupt occurs.

```

5      void BOD_ISR(void) interrupt 5
6      {
7          RSTSRC &= ~0x40; // clr BOIF at RSTSRC.6
8
9          BOD_flag = 1;     // make flag active
10
11         P2^=0xff;         // Blinky LEDs
12     }
13

```

## 4.2 Demo setup




Fig 1. Demo setup

## 4.3 Output information

When the power supply falls to lower than about 2.55 V, the BOD interrupt is triggered and debug information “BOD interrupt” will be sent to UART0. If the power supply is raised higher than 2.7 V, there will be no serial debug information.




Fig 2. Output information

## 5. Reference

- [1] LPC98x User Manual (UM10346) – Rev. 02
- [2] LPC98x Data Sheet – Rev. 01

## 6. Legal information

### 6.1 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

### 6.2 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft,

space or life support equipment, nor in applications where failure or malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on a weakness or default in the customer application/use or the application/use of customer's third party customer(s) (hereinafter both referred to as "Application"). It is customer's sole responsibility to check whether the NXP Semiconductors product is suitable and fit for the Application planned. Customer has to do all necessary testing for the Application in order to avoid a default of the Application and the product. NXP Semiconductors does not accept any liability in this respect.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

### 6.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are property of their respective owners.



7. Contents

1. Introduction .....3

2. BOD flash .....3

3. BOD reset and BOD interrupt.....3

4. BOD demo.....5

4.1 Demo introduction .....5

4.2 Demo setup.....6

4.3 Output information.....6

5. Reference .....7

6. Legal information .....8

6.1 Definitions .....8

6.2 Disclaimers.....8

6.3 Trademarks.....8

7. Contents.....9

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.