

MC68HC908GT16/8

Target Applications

- > Radar detectors
- > Industrial and home lighting
- > Security systems
- > Home appliances
- > Sensors
- > Electronic power meters
- > Wireless communication
- > PDA attachments

Overview

Freescale Semiconductor's MC68HC908GT16 and MC68HC908GT8 are fully integrated microcontrollers (MCUs) created to make system design easier by eliminating external peripherals wherever possible. The internal clock generator eliminates the need for an external clock source and helps reduce system costs. The integrated second-generation flash memory programs up to 100 times faster than prior flash solutions and offers in-application programming. Features include a synchronous serial peripheral interface (SPI), an asynchronous serial communications interface (SCI), an analog-to-digital converter (ADC), an autowake-up from stop feature, low-voltage inhibit (LVI) and a watchdog timer.

HC08 CPU	KBI
16 KB/8 KB Flash	8-ch., 8-bit ADC
512B RAM	SCI
LVI	SPI
COP	2 x 2-ch., 16-bit Timer
Internal Clock Generator	Up to 36 GPIO

Features

High-Performance 68HC08 CPU Core

- > 8 MHz bus operation at 5V operation for 125 ns minimum instruction cycle time
- > 4 MHz bus operation at 3V for 250 ns minimum instruction cycle time
- > Efficient instruction set, including multiply and divide
- > 16 flexible addressing modes, including stack relative with 16-bit stack pointer
- > Fully static, low-voltage, low-power design with wait and stop modes

Integrated Second-Generation Flash Memory

- > In-application reprogrammable
- > Extremely fast programming, encoding 64B in as fast as 2 ms
- > Flash programming across the 68HC08's full operating supply voltage with no extra programming voltage
- > 10K write/erase cycles minimum over temperature
- > Flexible block protection and security

Up to 36 Bidirectional Input/Output (I/O) Lines

- > 10 mA sink/source on all I/O pins
- > 15 mA sink capability on five I/O pins
- > Keyboard scan with selectable interrupts on eight I/O pins
- > Software programmable pull-ups on 23 I/O pins

Two Programmable 16-bit Timer Channels

- > 125 ns resolution at 8 MHz bus
- > Free-running counter or modulo up-counter

Internal Clock Generator

- > Software-selectable bus frequencies
- > Two percent accurate with trim capability
- > Clock monitor
- > Option to allow use of external clock source or external crystal/ceramic resonator

Benefits

- > Object code compatible with the 68HC05
- > Easy to learn and use architecture
- > C-optimized architecture provides compact code

- > Cost-effective programming changes and field software upgrades via in-application programmability and reprogrammability
- > ROM option available in place of flash
- > Reduces production programming costs through ultra-fast programming
- > Allows reprogrammable battery-powered applications
- > Byte-writable for data as well as program memory
- > Protects code from unauthorized reading and guards against unintentional writing/erasing of user-programmable segments of code

- > High-current I/O allows direct drive of LED and other circuits to eliminate external drivers and reduce system costs

- > Keyboard scan with programmable pull-ups eliminates external glue logic when interfacing to simple keypads

- > Each channel independently programmable for input capture, output compare or unbuffered pulse-width modulation (PWM)

- > Pairing timer channels provides a buffered PWM function

- > Eliminates the need and cost for an external clock source

- > Improved accuracy across temperature and voltage

Features

Benefits

Timebase Module

- > Eight user-selectable periodic real-time interrupts
- > Optionally operate in low-power stop mode

- > Provides autowake-up from low-power stop mode to maintain real-time clock or check external device status such as sensors

Serial Communications Interface

- > UART asynchronous communications system
- > Flexible baud rate generator
- > Double-buffered transmit and receive
- > Optional hardware parity checking and generation

- > Enables synchronous serial communications with peripheral devices

Serial Peripheral Interface

- > Full-duplex, three-wire synchronous transfers
- > Maximum master bit rate of 4 MHz for 8 MHz system clock

- > High-speed synchronous communication between multiple MCUs or between MCU and serial peripherals
- > Cost-effective serial peripheral expansion to applications including EEPROM, high-precision analog-to-digital and digital-to-analog converters, and real-time clocks

Computer Operating Properly (COP) Watchdog Timer

- > Issues reset in the event of runaway code

Selectable Trip Point Low-Voltage Inhibit (LVI)

- > Improves reliability by resetting the MCU when voltage drops below trip point
- > Two trip points allow optimum operation in both 5V and 3V nominal systems
- > Integration reduces system cost

8-bit Analog-to-Digital Converter (ADC)

- > 8 channels
- > Single conversion in 17 μ s

- > Fast, easy conversion from analog inputs, such as temperature, pressure and fluid levels, to digital values for CPU processing

Application Notes

AN1050 Designing for Electromagnetic Compatibility (EMC) with HCMOS Microcontrollers

AN1218 HC05 to HC08 Optimization

AN1219 M68HC08 Integer Math Routines

AN1259 System Design and Layout Techniques for Noise Reduction in MCU-Based Systems

AN1263 Designing for Electromagnetic Compatibility with Single-Chip Microcontrollers

AN1705 Noise Reduction Techniques for Microcontroller-Based Systems

AN1752 Data Structures for 8-bit MCUs

AN1831 Using MC68HC908 On-Chip Flash Programming Routines

AN1837 Non-Volatile Memory Technology Overview

AN2093 Creating Efficient C Code for the MC68HC08

EB366 In-Circuit Programming of 68HC908GP32 Flash Memory

Learn More: For more information about Freescale's products, please visit www.freescale.com.

*Price indicated is MSRP.

**Subject to license and registration.

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners. This product incorporates SuperFlash® technology licensed from SST.

© Freescale Semiconductor, Inc. 2006

Document Number: 68HC908GT16FS

REV 1

Cost-Effective Development Tools

For more information on development tools, please refer to the Freescale Development Tool Selector Guide (SG1011).

FSICEKITGPGT
\$2,495*

Complete FSICE high-performance emulator kit; includes emulator module, cables, head adapters and programming adapters

M68EML08GPGT
\$495*

Emulation module for FSICE system

M68CYCLONEPRO
\$499*

HC08/HCS08/HC12/HCS12 stand-alone flash programmer or in-circuit emulator, debugger, flash programmer; USB, serial or Ethernet interface options

USBMULTILINK08
\$99*

Universal HC08 in-circuit debugger and flash programmer; USB PC interface

M68CPA08QF324448
\$199*

Programming adapter for MON08 cables and single MCU: 32-pin 0.8 mm QFP packages, 44-pin 0.8 mm QFP packages and 48-pin 0.5 mm QFP packages

CWX-H08-SE
Free**


CodeWarrior™ Special Edition for HC(S)08 MCUs; includes integrated development environment (IDE), linker, debugger, unlimited assembler, Processor Expert™ auto-code generator, full-chip simulation and 16 KB C compiler

Package Options

Part Number	Package	Temp. Range
MC68HC908GT16CFB	44 QFP	-40°C to +85°C
MC68HC908GT16CB	42 SDIP	-40°C to +85°C
MC68HC908GT8CFB	44 QFP	-40°C to +85°C
MC68HC908GT8CB	42 SDIP	-40°C to +85°C

Please contact a Freescale Sales representative for ordering information on ROM devices.

42-Pin Plastic DIP



44-Lead QFP

