



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
1.1	Original	5/3/02	MWN
1.1A	Changed Rev B to C PK90681C-CFR	5/21/02	DM

**NOTES:**

- 1 All items listed are to be appropriately packed in the specified case so that the components won't get damaged in transit.
- 2 All PCB assemblies are to be individually packaged in an appropriately sized ESD protection bag. A label containing the PWA P/N and BOM Revision must be attached on outside of bag.

IDL Source File Location: /data1/vobs/Manufacturing\_Release\_vbs/10793\_M5407C3/MfgPackage

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO MOTOROLA AND SHALL NOT BE USED FOR ENGINEERING DESIGN, PROCUREMENT OR MANUFACTURE IN WHOLE OR IN PART WITHOUT CONSENT OF MOTOROLA.

**MOTOROLA**

SEMICONDUCTOR PRODUCTS SECTOR  
6501 William Cannon Drive West  
Austin, Texas 78735

		APPROVALS	DATE	TITLE		
		DRAWN		FINAL ASSEMBLY FOR MODEL NO.		
		Michael Norman	5/3/02	<b>M5407C3</b>		
		CHECKED		Motorola MCF5407 Processor Evaluation Board		
None		PRODUCT MARKETING MANAGER		SIZE	CAD FILE NAME	DWG. NO.
NEXT ASSY	USED ON			A	I10793.xls	01A10793I
APPLICATION		MANUFACTURING	Revised	REV		
		David Malanchuk	5/21/02	1.1A		
INDENTURE DRAWING						



**BEFORE KIT ASSEMBLY:**

1. Print packing list M5407C3\_PKL\_Rev\_B.pdf (Item #11) in black and white on 8.5"x11" white paper
2. Download and print TIC Contact Information (Item #14) in black and white, one page, double sided (8.5"x11")

**KIT PACKING INSTRUCTIONS:**

1. Assemble Motorola boxes and insert cardboard divider.
2. Place 1" X 8" X 13" piece of convoluted anti-static foam into right half segment of the box.( convoluted side up )
3. Place DB9, DB25, and P&E ColdFire BDM cables in right half.
4. Place 1" x 8" x 13" piece of convoluted anti-static foam on top of cables.( convoluted side down )
5. Place Metrowerks and 3rd party software tools and/or information in right half.
6. Place 1" x 8" x 13" piece of anti-static foam on top of software.
7. Place MCF5407 ColdFire Integrated Microprocessor User's Manual on bottom left side.
8. Place ColdFire Family Programmers Reference Manual on top of Processor User's Manual
9. Place 1" x 8" x 13" piece of anti-static foam on top of manual.
10. Place packaged RE10793B on top of anti-static foam. MCF5407 evaluation board packed in anti-static bag and labeled "RE10793B Rev 1.1".
11. Place 1" x 8" x 13" piece of anti-static foam on top of board.
12. Place M5407C3 User's Manual on top of foam.
13. Place 1/2" x 9" x 13" anti-static section with cut out window over manual.

**FINAL INSPECTION:**

1. Inspect contents and verify that all items on the packing list are present.
2. Place packing list on top of right half.
3. Close box lid after inspection is complete.
4. Place barcode label on right front side of box.
5. Place CE Inspection label on left front side of box.

<p><b>MOTOROLA</b>          SEMICONDUCTOR PRODUCTS SECTOR          6501 William Cannon Drive West          Austin, Texas 78735</p>			
<p>TITLE FINAL ASSEMBLY FOR MODEL NO.  <b>M5407C3</b>          Motorola MCF5407 Processor Evaluation Board</p>			
SIZE	CAD FILE NAME	DWG. NO.	REV
A	I10793.xls	<b>01A10793I</b>	<b>1.1A</b>
INDENTURE DRAWING		5/21/02	



INDENTURE DRAWING		MOTOROLA		DWG NO.	01A10793I
FOR MODEL		M5407C3		Rev	1.1A
	01A10793I	RE10793I	FINAL ASSEMBLY FOR MODEL M5407C3		Date
				5/21/02	
ITEM	DRAWING NO.	PART NO.	DESCRIPTION	QTY	REMARKS
1	01A10793A	RE10793B Rev 1.1	Revision 1.1 of Printed Wiring Board Assembly packaged in anti-static bag, <b>Label on outside of bag must state "RE10793B Rev 1.1"</b>	1	Matrix Design & Manufacturing (512) 385-9144 or approved alternate
2		22-122 or 23-SC-MO	Cable: DB9 M/F RS-232 Serial Data Cable, 6 ft.	1	Krista Micro or equivalent alternate
2 alt.		CAB-ST9FM-06	Cable: DB9 M/F RS-232 Serial Data Cable, 6 ft.		Manhattan
3		22-027	Cable: DB25 M/F; RS-232 Parallel Port Interface Extension Cable, 6 ft.	1	Krista Micro or equivalent alternate
3 alt.		AE1012-ND	Cable: DB25 M/F; RS-232 Parallel Port Interface Extension Cable, 6 ft.		DigiKey
4		CABLE_CF	Cable: ColdFire Shielded Interface Cable (wiggler) ; Rev F or later	1	P&E Micro, 617-353-9206
5		M5407C3UM/D	Book: M5407C3 User's Manual	1	Motorola LDC
6		MCF5407UM/D	Book: MCF5407 ColdFire Integrated Microprocessor User's Manual	1	Motorola LDC
7		CFPRM/D	Book: ColdFire Family Programmers Reference Manual Rev. 2	1	Motorola LDC
8		MOT-PDC	Label: Bar Code Identify: MPN:M5407C3 LOT, DTE, QTY	1	Motorola PDC; See Doc # 12MRB45322B
9		MOT-CE	Label: CE Mark	1	Marking Systems, Inc. 972-475-0770
10	41ATB50784P	50784P005	Packaging: Box with Motorola Logo, 17.5" x 13" x 4.25"	1	Capital City Container or approved alternate
11		001-1501	Packaging: 6-Piece Anti-static ColdFire Foam Set	1	Texas Foam
12		M5407C3_PKL_Rev_B	Document: M5407C3 Packing List; Print black and white (8 1/2 x 11)	1	Print from file: M5407C3_PKL_Rev_A.pdf
13		WNTYCARD1YMOT/D	Document: 1 year Warranty / Registration Card	1	Motorola LDC
14		PK90681C-CFR	Document: Metrowerks CodeWarrior for ColdFire Folder containing CodeWarrior evaluation CD, quick start guide, datasheet, etc. (black folder)	1	Metrowerks
15		BR1530BW/D	Document: "Technical Information Center for Motorola Semiconductor Products" <a href="http://e-www.motorola.com">http://e-www.motorola.com</a> Click on Documentation Library / Literature Services / General Search Print out black and white one page double sided (8 1/2 x 11)	1	Motorola LDC
16		3rd Party Tools	Development tool evaluations and/or information from various vendors.		