

1. THIS DRAWING SPECIFIES THE REQUIREMENTS FOR A PRINTED WIRING BOARD IN ACCORDANCE WITH SPECIFICATION IPC-A-600 CLASS 2 (LATEST REVISION).

2. THE PWB MUST BE LEAD FREE ASSEMBLY PROCESS COMPATIBLE AND MUST BE ABLE TO HANDLE A MINIMUM OF 5 CYCLES AT 260 DEGREES CELSIUS FOR 10 SECONDS.

3. BASE MATERIAL - LAMINATE AND PREPREG SHALL MEET IPC-4101B-26, 83 or 98
Tg - MUST BE GREATER THAN OR EQUAL TO 150 DEGREES CELSIUS.
Td - MUST BE GREATER THAN OR EQUAL TO 330 DEGREES CELSIUS.

4. COPPER FOIL WEIGHT - SEE STACKUP DETAIL 'A'

5. CHARACTERISTIC IMPEDANCE - NOT APPLICABLE

6. MINIMUM CONDUCTIVE WIDTH/SPACING TO BE .005"/.005"

7. PLATING FINISH - BOTH SIDES ENIG (ELECTROLESS NICKEL IMMERSION GOLD):
.05080-.232 MICRON (2-8 MICROINCH) OF GOLD OVER
2.540-6.350 MICRON (100-250 MICROINCH) OF NICKEL.

8. ALL THROUGH HOLE VIAS MAY BE PLATED SHUT.

9. SOLDERMASK - ORANGE COLOR (TAIYO OR EQUIVALENT), BOTH SIDES.
MODIFICATION OF SOLDERMASK IS NOT ALLOWED WITHOUT WRITTEN PERMISSION FROM FREESCALE.

10. SILKSCREEN - WHITE EPOXY INK, BOTH SIDES, NO SILK ON PADS.

11. ELECTRICAL TEST - 100% IPCD356.

12. PRINTED WIRING BOARD IS TO BE INDIVIDUALLY BAGGED.

13. DRC'S MUST BE RUN ON THE GERBER BEFORE BUILDING BOARDS, UNLESS PRIOR APPROVAL IS GIVEN IN WRITING BY FREESCALE.

14. TEARDROPS MAYBE ADDED AT THE FAB HOUSE TO ALL SIGNAL LAYERS.

15. TWO SOLDER SAMPLES TO BE PROVIDED.

16. BASIC GRID INCREMENT AT 1:1 IS .0001.

17. SUPPLIER MARKINGS - ON SOLDER SIDE ONLY, WHERE SHOWN.
- MUST BE UL RECOGNIZED AND MUST HAVE AN ID THAT CONFORMS TO UL94V-0

18. THE PWB WILL BE MARKED AS LEAD FREE BY USE OF AN INK STAMP (96)

19. THE PWB WILL BE MARKED AS LEAD FREE PROCESS COMPATIBLE BY USE OF AN INK STAMP (260°C)


20. ALL PLATED AND NON-PLATED THROUGH HOLES ARE TO BE DRILLED AT PRIMARY DRILL STEP.
ALL HOLE LOCATION TOLERANCES ARE TO BE $\pm .002$ IN REFERENCE TO THE PRIMARY DATUM.

21. FINISHED PCB MUST BE PANELIZED FOR ASSEMBLY ACCORDING TO CONTRACT MANUFACTURERS REQUIREMENTS. THE ADDITION OF RAILS AND .125" NON-PLATED TOOLING HOLES ARE AT THE DISCRETION OF CONTRACT MANUFACTURER. PANELIZATION MUST BE APPROVED BY CONTRACT MANUFACTURER.

```

22. INTENTIONAL SHORTS AT:
    SH1 VDD_IN & VDD_8491
    SH2 SDA_S & SDA
    SH3 SCL_S & SCL
    SH4 GND_1 & GND


```



—0.062" THICK +/-10%

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	8.0	+0.0/-8.0	PLATED	36
⊙	40.0	+3.0/-3.0	PLATED	8
◆	25.0	+2.0/-2.0	NON-PLATED	1

8

		FINISHED Cu WEIGHT
	LAYER 1 L1_PS	1 oz.
	LAYER 2 L2_SS	1 oz.

DETAIL A
LAYER STACKUP
SCALE: NONE

PART NO. 170-28992 THIS DOCUMENT CONTAINS INFORMATION RELATIVE TO FREESCALE AND SHALL NOT BE USED FOR PROMOTING DESIGN ENGAGEMENT OR FREESCALE IN WHOLE OR IN PART WITHOUT THE CONSENT OF FREESCALE.		FREESCALE	
() PURE (PUBLIC INFORMATION) (X) FPD (FREESCALE INTERNAL USE ONLY) () FCP (FREESCALE CONFIDENTIAL, PROPRIETARY)		6501 WILLIAM CANNON DRIVE WEST AUSTIN, TEXAS 78735 USA	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: DECIMALS .010 .005 .003 .002 ✓ ALL ALL DIMENSIONS SURFACES BEARING ALL SHARP EDGES AND CORNERS, RADIUS ROUNDS. DIMENSIONS NOT TO SCALE. THESE DIMENSIONS ORTHOGRAPHIC PROJECTION.		PRINTED WIRING BOARD BRKST5BC-A8491	
APPROVALS DATE DESIGN SAHIL C 9/10/15 CHECKED DESIGN ENGINEER SAHIL C 9/10/15		SIZE CAD FILE NAME Dwg. NAME D LAY-28992	FAB-28992
SCALE 1/1		DO NOT SCALE DRAWING	SHEET 1 OF 1